

ThinkCentre M73 Tiny Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® Celeron®, Intel Pentium®, or 4th Generation Intel Core™ i3 / i5 / i7 Processors						Manageability	None																																																																														
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Frequency (Base/Max)</th> <th>Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Celeron G1820T</td> <td>2 / 2</td> <td>2.4 GHz</td> <td>2 MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Celeron G1840T</td> <td>2 / 2</td> <td>2.5 GHz</td> <td>2 MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Pentium G3220T</td> <td>2 / 2</td> <td>2.6 GHz</td> <td>3 MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Pentium G3240T</td> <td>2 / 2</td> <td>2.7 GHz</td> <td>3 MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Pentium G3420T</td> <td>2 / 2</td> <td>2.7 GHz</td> <td>3 MB</td> <td>DDR3-1600</td> <td>Intel HD</td> </tr> <tr> <td>Core i3-4130T</td> <td>2 / 4</td> <td>2.9 GHz</td> <td>3 MB</td> <td>DDR3-1600</td> <td>HD 4400</td> </tr> <tr> <td>Core i3-4150T</td> <td>2 / 4</td> <td>3 GHz</td> <td>3 MB</td> <td>DDR3-1600</td> <td>HD 4400</td> </tr> <tr> <td>Core i5-4460T</td> <td>4 / 4</td> <td>1.9 GHz / 2.7 GHz</td> <td>6 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> <tr> <td>Core i5-4570T</td> <td>2 / 4</td> <td>2.9 GHz / 3.6 GHz</td> <td>4 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> <tr> <td>Core i5-4590T</td> <td>4 / 4</td> <td>2 GHz / 3 GHz</td> <td>6 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> <tr> <td>Core i7-4765T</td> <td>4 / 8</td> <td>2 GHz / 3 GHz</td> <td>8 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> <tr> <td>Core i7-4785T</td> <td>4 / 8</td> <td>2.2 GHz / 3.2 GHz</td> <td>8 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> </tbody> </table>						Processor	Cores / Threads	Frequency (Base/Max)	Cache	Memory Types	Integrated Graphics	Celeron G1820T	2 / 2	2.4 GHz	2 MB	DDR3-1333	Intel HD	Celeron G1840T	2 / 2	2.5 GHz	2 MB	DDR3-1333	Intel HD	Pentium G3220T	2 / 2	2.6 GHz	3 MB	DDR3-1333	Intel HD	Pentium G3240T	2 / 2	2.7 GHz	3 MB	DDR3-1333	Intel HD	Pentium G3420T	2 / 2	2.7 GHz	3 MB	DDR3-1600	Intel HD	Core i3-4130T	2 / 4	2.9 GHz	3 MB	DDR3-1600	HD 4400	Core i3-4150T	2 / 4	3 GHz	3 MB	DDR3-1600	HD 4400	Core i5-4460T	4 / 4	1.9 GHz / 2.7 GHz	6 MB	DDR3-1600	HD 4600	Core i5-4570T	2 / 4	2.9 GHz / 3.6 GHz	4 MB	DDR3-1600	HD 4600	Core i5-4590T	4 / 4	2 GHz / 3 GHz	6 MB	DDR3-1600	HD 4600	Core i7-4765T	4 / 8	2 GHz / 3 GHz	8 MB	DDR3-1600	HD 4600	Core i7-4785T	4 / 8	2.2 GHz / 3.2 GHz	8 MB	DDR3-1600	HD 4600	Security chip	None
	Processor	Cores / Threads	Frequency (Base/Max)	Cache	Memory Types	Integrated Graphics																																																																																
	Celeron G1820T	2 / 2	2.4 GHz	2 MB	DDR3-1333	Intel HD																																																																																
	Celeron G1840T	2 / 2	2.5 GHz	2 MB	DDR3-1333	Intel HD																																																																																
	Pentium G3220T	2 / 2	2.6 GHz	3 MB	DDR3-1333	Intel HD																																																																																
	Pentium G3240T	2 / 2	2.7 GHz	3 MB	DDR3-1333	Intel HD																																																																																
	Pentium G3420T	2 / 2	2.7 GHz	3 MB	DDR3-1600	Intel HD																																																																																
	Core i3-4130T	2 / 4	2.9 GHz	3 MB	DDR3-1600	HD 4400																																																																																
	Core i3-4150T	2 / 4	3 GHz	3 MB	DDR3-1600	HD 4400																																																																																
	Core i5-4460T	4 / 4	1.9 GHz / 2.7 GHz	6 MB	DDR3-1600	HD 4600																																																																																
	Core i5-4570T	2 / 4	2.9 GHz / 3.6 GHz	4 MB	DDR3-1600	HD 4600																																																																																
	Core i5-4590T	4 / 4	2 GHz / 3 GHz	6 MB	DDR3-1600	HD 4600																																																																																
Core i7-4765T	4 / 8	2 GHz / 3 GHz	8 MB	DDR3-1600	HD 4600																																																																																	
Core i7-4785T	4 / 8	2.2 GHz / 3.2 GHz	8 MB	DDR3-1600	HD 4600																																																																																	
						Security features	<ul style="list-style-type: none"> Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password 																																																																															
						Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), Lenovo logo <i>Some:</i> Lenovo Slim USB Keyboard (USB connector), black, Lenovo logo																																																																															
						Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																																																																															
						Mechanical	Tiny (1L), business black color; metal case																																																																															
							<table border="1"> <tr> <td>M73 Tiny only</td> <td>7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration</td> </tr> <tr> <td>M73 Tiny with VESA mount & optical box</td> <td>7.2" W X 7.2" D X 2.55" H 184mm W X 182mm D X 65mm H 5.1lb (2.3 kg), weight may vary by configuration</td> </tr> </table>	M73 Tiny only	7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration	M73 Tiny with VESA mount & optical box	7.2" W X 7.2" D X 2.55" H 184mm W X 182mm D X 65mm H 5.1lb (2.3 kg), weight may vary by configuration																																																																											
M73 Tiny only	7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration																																																																																					
M73 Tiny with VESA mount & optical box	7.2" W X 7.2" D X 2.55" H 184mm W X 182mm D X 65mm H 5.1lb (2.3 kg), weight may vary by configuration																																																																																					
						VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm																																																																															
						Floor Stand	Optional system floor stand for vertical orientation																																																																															
						Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models)																																																																															
						Limited warranty ³	<i>Some:</i> 1-year, depot repair service <i>Some:</i> 1-year or 3-years, limited onsite service <i>Some:</i> 3-years, limited onsite service, OID (Onsite International Delivery) / <i>For Lenovo service upgrade options, please go to S-TC sheet</i>																																																																															
						Preload	<i>Some:</i> Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility PC Device Stage Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Evernote® Microsoft® Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Nitro Pro 																																																																															
							<i>Some:</i> Genuine Windows® Embedded Standard 7 (WES 7) <i>Some:</i> Genuine Windows Embedded 8 Standard (WE8S) <i>Some:</i> LeTOS (Lenovo Terminal Operating System, Linux-based) Preloaded applications (only some listed) - Windows Embedded only: <ul style="list-style-type: none"> Intel Trusted Execution Engine Interface RDP Client (RDP 8 support) Citrix Receiver VMware Client Internet Explorer Java 8 Adobe Flash Player Microsoft® Silverlight Echo Agent (client for LTM) UltraVnc (WE8S) Adobe Acrobat Reader DC - LeTOS only: <ul style="list-style-type: none"> xFreeRDP Citrix ICA Client VMware View Client Java Mozilla Firefox NX NoMachine Client X11 Client VDI-In-A-Box Java Client AnyConnect VPN Client 																																																																															
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), System automatically clocks down for processors with 1333MHz DDR3 memory controller																																																																																					
Disk	<i>Some:</i> 8GB or 16GB / DOM (Disk On Module) Card <i>Some:</i> Hard disk, 2.5" Wide, 5400 rpm or 7200 rpm <i>Some:</i> 500GB (5400 rpm) Solid State Hybrid Drive (SSHD) / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide or M.2 <i>Some:</i> external USB optical box with slim DVD-ROM, 12.7mm high, tray-in <i>Some:</i> external USB optical box with slim DVD±RW, 12.7mm high, tray-in <i>Some:</i> external USB optical box with slim DVD±RW, 9.5mm high, tray-in, for TIO 23																																																																																					
Optical	None																																																																																					
Onboard SATA Media reader	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar																																																																																					
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports up to dual independent display; <i>Max resolution:</i> 3840x2160 (DP)@60Hz [HD 4x00]; 2560x1600 (DP)@60Hz [Intel HD]; 1920x1200 (VGA)@60Hz (Reduced Blanking)																																																																																					
DP cable	None																																																																																					
Chipset	Intel H81 Chipset																																																																																					
Front ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)																																																																																					
Rear ports	Three USB 2.0 (optional external optical box or external I/O box occupies one specific USB 2.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort, one optional port (USB 2.0 / serial on selected models)																																																																																					
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 2.0 port																																																																																					
Audio support	High Definition (HD) Audio, Realtek ALC283 / internal speaker (1.5 watt)																																																																																					
WLAN ¹³	<i>Some:</i> 11ac/b/g/n wireless, PCIe Half Mini Card, Broadcom BCM4352, dual band (2.4/5GHz), Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 <i>Some:</i> 11b/g/n, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 7260, Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo 4.0 adapter, 2x2																																																																																					
Bluetooth™	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter																																																																																					
Ethernet	Gigabit ethernet port, Intel I217-V, Wake on LAN®																																																																																					
Modem	None																																																																																					
Environment	ENERGY STAR® 6.0 (Need Windows OS); EPEAT™ Gold rating (Need Windows OS); GREENGUARD® certified; RoHS-compliant; Cisco EnergyWise compatible																																																																																					
Accessories	For compatible accessories, please go to TC-AQP sheet																																																																																					

See footnotes for more detailed information