

Item enabled by default

HEX code will be converted in base 64 [Hex] Required field (\*)

DSDT RenameDevices

Patches

Comment	Find* [HEX]	Replace [HEX]	TgtBridge [HEX]	Disabled
HDAS to HDEF	48444153	48444546		<input type="checkbox"/>
EC0_ to EC__	4543305F	45435F5F		<input type="checkbox"/>
H_EC to EC__	485F4543	45435F5F		<input type="checkbox"/>
HECI to IMEI	48454349	494D4549		<input type="checkbox"/>

List Of Patches

Fixes

- AddDTGP
- FixDarwin
- FixShutdown
- AddMCHC
- FixHPET
- FakeLPC
- FixIPIC
- FixSBUS
- FixDisplay
- FixIDE
- FixSATA
- FixFirewire
- FixUSB
- FixLAN
- FixAirport
- FixHDA

Drop OEM\_DSM

- ATI
- IntelGFX
- NVidia
- HDA
- HDMI
- LAN
- WIFI
- USB
- Firewire
- IDE
- SATA
- LPC
- SmBUS

1 2

- Debug
- Rtc8Allowed
- ReuseFFFF
- SlpSmiAtWake
- SuspendOverride

DSDT.aml  
DSDT name

Drop Tables

Signature*	Type/key	String[TableId]/Number[Length]
SSDT	TableId	Cpu0Ist

SSDT

- Double First State
- Drop OEM
- Use SystemIO
- NoOemTableId
- NoDynamicExtract
- Plugin Type
- PLimit Dict
- UnderVolt Step
- Min Multiplier
- Max Multiplier
- C3 Latency
- EnableC2
- EnableC4
- EnableC6
- EnableC7

Generate Options

- Generate PStates
- Generate CStates
- APSN
- APLF
- PluginType

- Patch APIC
- Smart UPS
- Halt Enabler
- DisableASPM
- AutoMerge
- FixHeaders
- FixMCFG

0x64  
Reset Address

0xFE  
Reset Value

DisabledAML

[Empty list box]

SortedOrder

[Empty list box]

SECTIONS

- Acpi
- Boot
- Boot Graphics
- Cpu
- Devices
- Disable Drivers
- Gui
- Graphics
- Kernel and Kext Patches
- Rt Variables
- SMBIOS
- System Parameters

TOOLS

- Mount EFI
- Boot.log
- Generate Config
- Themes Editor
- Install/Update Clover
- Install Drivers
- NVRAM
- HEX converter
- Text Mode