

Erledigt Fragen zum CPU Wechsel

Beitrag von „VANTOM“ vom 14. Mai 2014, 07:01

```
Character: 05/07/2009 Compiled for 32/64-bit by Taruga
**** [IOBluetoothHostControllerUSBTransport][start] -- completed -- result = TRUE -- 0xa800 ****
**** [BroadcomBluetoothHostControllerUSBTransport][start] -- Completed -- 0xa800 ****
utun_ctl_connect: creating interface utun0
flow_divert_kctl_disconnect (0): disconnecting group 1
VDASStartup: Official
WARNING: IOPlatformPluginUtil : getCPUIDInfo: this is an unknown CPU model 0x3a
-- power management may be incomplete or unsupported
VDAGK100HAL loaded and registered
Sound assertion in AppleHDACodecGeneric at line 352
Sound assertion in AppleHDACodecGeneric at line 352
init
probe
start
SMC::smcReadKeyAction ERROR: kSMCReadKeyComm/kSMCReadKeyWithSMCComm failed for key DSK0 (kSMCSuccess)
SMC::smcReadKeyAction ERROR: kSMCReadKeyComm/kSMCReadKeyWithSMCComm failed for key DSK1 (kSMCSuccess)
MSDS has arrived
[IOBluetoothHCIController][staticBluetoothHCIControllerTransportShowsUp] -- Received Bluetooth Controller
Sound assertion in AppleHDAEngine at line 581
[IOBluetoothHCIController][start] -- completed
[IOBluetoothHCIController::setConfigState] calling registerService
**** [IOBluetoothHCIController][protectedBluetoothHCIControllerTransportShowsUp] -- Connected to the transp

TUFS: starting (version 2012.4.17, x86_64 (10.6+), built Apr 17 2012, 11:40:41)
[BNBMouseDevice::init][80.14] init is complete
[BNBTrackpadDevice::init][80.14] init is complete
[BNBMouseDevice::handleStart][80.14] returning 1
[AppleMultitouchHIDEventDriver::start] entered
[AppleMultitouchDevice::start] entered
[BNBTrackpadDevice::handleStart][80.14] returning 1
[AppleMultitouchHIDEventDriver::start] entered
[AppleMultitouchDevice::start] entered
SMC::smcReadKeyAction ERROR MSDS kSMCbadArgumentError(0x89) fKeyHashTable=0x0xfffff802000da00
```

Sorry hier das Bild. War nicht zuhause....

Sent from my iPhone using Tapatalk