

Erledigt

Asus Zenbook UX32VD clover

Beitrag von „keiner99“ vom 28. Juli 2014, 23:05

Hallo!

Möchte auf einem Asus Zenbook UX32VD [clover installieren](#). Hab mir jetzt einmal einen Clover mavericks stick erstellt und von diesem gebootet. jedoch bleibt er gleich am anfang stecken:

```
Longterm timer threshold: 1000 ms
PMAP: PCID enabled
PMAP: Supervisor Mode Execute Protection enabled
Darwin Kernel Version 13.2.0: Thu Apr 17 23:03:13 PDT 2014; root:xnu-2422.100.13~1/RELEASE_X86_64
vm_page_bootstrap: 960175 free pages and 80209 wired pages
kext submap [0xffffffff7f807a9000 - 0xffffffff8000000000], kernel text [0xffffffff8000200000 - 0xffffffff80007a9000]
zone leak detection enabled
"vm_compressor_mode" is 4
standard timeslicing quantum is 10000 us
standard background quantum is 2500 us
mig_table_max_displ = 74
TSC Deadline Timer supported and enabled
"name" not a kext
"FailedCLUT" not a kext
"FailedImage" not a kext
NullCPUPowerManagement::init: properties=0xffffffff800f6b4b40
NullCPUPowerManagement::start
AppleACPICPU: ProcessorId=1 LocalApicId=0 Enabled
AppleACPICPU: ProcessorId=2 LocalApicId=2 Enabled
AppleACPICPU: ProcessorId=3 LocalApicId=1 Enabled
AppleACPICPU: ProcessorId=4 LocalApicId=3 Enabled
calling mpo_policy_init for TMSafetyNet
Security policy loaded: Safety net for Time Machine (TMSafetyNet)
calling mpo_policy_init for Sandbox
Security policy loaded: Seatbelt sandbox policy (Sandbox)
calling mpo_policy_init for Quarantine
Security policy loaded: Quarantine policy (Quarantine)
Copyright (c) 1982, 1986, 1989, 1991, 1993
The Regents of the University of California. All rights reserved.

MRC Framework successfully initialized
using 16384 buffer headers and 10240 cluster IO buffer headers
AppleKeyStore starting (BUILT: Apr 17 2014 23:36:27)
FakeSMCKeyStore: started
IOAPIC: Version 0x20 Vectors 64:87
ACPI: sleep states S3 S4 S5
pci (build 23:24:05 Apr 17 2014), flags 0x63000, pfm64 (36 cpu) 0xf80000000, 0x80000000
[ PCI configuration begin ]
FakeSMC v6.0.1123 Copyright 2014 natkas, slice, usr-sse2, kozlek, navi, The KING, RehabMan. All rights reserved.
FakeSMC: 13 preconfigured keys added
FakeSMC: 5 keys exported by Clover EFI
SMC: successfully initialized
console relocated to 0xfa0000000
[ PCI configuration end, bridges 4, devices 14 ]
```

jemand ne idee wie ich diesen Fehler beheben kann?

keiner99 🍌