

## **Erledigt** MacPro6,1 und KP

**Beitrag von „forrest“ vom 16. Oktober 2014, 23:30**

Hallo noch mal,

ich komme leider nicht weiter. In den Safemode kann ich booten. Aber normal kommt immer dieser Fehler.

Thu Oct 16 23:12:15 2014

panic(cpu 6 caller 0xfffff7f81c52444): allocMem: failed assertion 'addr'

Backtrace (CPU 6), Frame : Return Address

0xfffff81f030bc00 : 0xfffff8000222f79

0xfffff81f030bc80 : 0xfffff7f81c52444

0xfffff81f030bc90 : 0xfffff7f81c63112

0xfffff81f030bcd0 : 0xfffff7f81c6362d

0xfffff81f030bd50 : 0xfffff7f81c63a58

0xfffff81f030bd90 : 0xfffff7f81c63b19

0xfffff81f030bdc0 : 0xfffff7f81c56d27

0xfffff81f030be20 : 0xfffff7f81634b8b

0xfffff81f030be50 : 0xfffff800069591f

0xfffff81f030bea0 : 0xfffff80006954df

0xfffff81f030bf30 : 0xfffff80006910b9

0xfffff81f030bf70 : 0xfffff8000696033

0xfffff81f030bf0 : 0xfffff80002d7607

Kernel Extensions in backtrace:

com.apple.iokit.IOAudioFamily(1.9.7f2)[092DA230-DD20-3369-A32B-E162A496C638]@0xfffff7f81631000->0xfffff7f81667fff

dependency: com.apple.kext.OSvKernDSPLib(1.14)[7C60EDB3-7527-3412-B424-C9A667A65B92]@0xfffff7f8161f000

org.voodoo.driver.VoodooHDA(2.8.6)[00000000-0000-0000-0000-000000000000]@0xfffff7f81c50000->0xfffff7f81c76fff

dependency: com.apple.iokit.IOAudioFamily(1.9.7fc2)[092DA230-DD20-3369-A32B-E162A496C638]@0xfffff7f81631000

dependency: com.apple.iokit.IOPCIFamily(2.9)[2852ACFE-FD28-3C37-9B39-885201BB8D25]@0xfffff7f808bf000

BSD process name corresponding to current thread: kernel\_task

Boot args: slide=0 -v

Mac OS version:

Not yet set

Kernel version:

Darwin Kernel Version 13.4.0: Sun Aug 17 19:50:11 PDT 2014; root:xnu-2422.115.4~1/RELEASE\_X86\_64

Kernel UUID: XXXXXXXX

System model name: MacPro3,1 (Mac-F42C88C8)

System uptime in nanoseconds: 367152561

last loaded kext at 364176899: com.insanelXmac.driver.AppleIntelE1000e 2.4.14 (addr 0xfffff7f8112e000, size 172032)

loaded kexts:

com.insanelXmac.driver.AppleIntelE1000e 2.4.14

org.voodoo.driver.VoodooHDA 2.8.6

org.hwsensors.driver.CPUSensors 1290

org.netkas.driver.FakeSMC 1290

com.apple.driver.AppleAHCIPort 3.0.5

com.apple.driver.AppleUSBXHCI 683.4.0

com.apple.driver.AppleUSBHCI 660.4.0

com.apple.driver.AppleACPIButtons 2.0

com.apple.driver.AppleHPET 1.8

com.apple.driver.AppleACPIEC 2.0

com.apple.driver.AppleRTC 2.0

com.apple.driver.AppleSMBIOS 2.1

com.apple.driver.AppleAPIC 1.7

com.apple.nke.applicationfirewall 153

com.apple.security.quarantine 3

com.apple.iokit.IONetworkingFamily 3.2

com.apple.iokit.IOAHCIFamily 2.6.5

com.apple.iokit.IOUSBFamily 686.4.1

com.apple.iokit.IOAudioFamily 1.9.7fc2

com.apple.kext.OSvKernDSPLib 1.14

com.apple.driver.AppleEFINVRAM 2.0

com.apple.driver.AppleEFIRuntime 2.0

com.apple.iokit.IOHIDFamily 2.0.0

com.apple.iokit.IOSMBusFamily 1.1

com.apple.security.sandbox 278.11.1

com.apple.kext.AppleMatch 1.0.0d1

com.apple.security.TMSafetyNet 7

com.apple.driver.AppleKeyStore 2

com.apple.driver.DiskImages 371.1

com.apple.iokit.IOStorageFamily 1.9

com.apple.iokit.IOReportFamily 23

com.apple.driver.AppleFDEKeyStore 28.30

com.apple.driver.AppleACPIPlatform 2.0

com.apple.iokit.IOPCIFamily 2.9

com.apple.iokit.IOACPIFamily 1.4

com.apple.kec.pthread 1

com.apple.kec.corecrypto 1.0

Model: MacPro3,1, BootROM MP31.006C.B05, 4 processors, Intel Core i7, 3.1 GHz, 16 GB, SMC 1.30f3

Graphics: Intel HD Graphics 4600, Intel HD Graphics 4600, Built-In

Memory Module: BANK 0/DIMM1, 8 GB, DDR3, 1600 MHz, Crucial Technology, BLS8G3D1609ES2LX0

Memory Module: BANK 0/DIMM3, 8 GB, DDR3, 1600 MHz, Crucial Technology, BLS8G3D1609ES2LX0

Bluetooth: Version 4.2.7f3 14616, 3 services, 22 devices, 0 incoming serial ports

Network Service: Ethernet, Ethernet, en0

Serial ATA Device: Samsung SSD 840 EVO 250GB, 250,06 GB

USB Device: Hub

USB Device: Hub

USB Device: Hub

USB Device: Hub

USB Device: USB Receiver

USB Device: Hub

USB Device: USB2.0 Hub

USB Device: BT2.0

Thunderbolt Bus:

*Wie kriege ich denn die zwei Dinger weg?*

org.voodoo.driver.VoodooHDA

org.netkas.driver.FakeSMC 1290

Vielen Dank & viele Grüße  
forrest