

Version 1479m

Beitrag von „griven“ vom 21. Februar 2016, 23:22

Hier die OzmosisDefaults aus der Version 1479m. Im Bereich Defaults:4D1FDA02-38C7-4A6A-9CC6-4BCCA8B30102 wurden bereits die für den Betrieb von iMessage und Facetime nötigen Keys eingefügt zudem ist der Bereich für die Ablage von Bootargs ebenfalls eingefügt worden. Alle möglichen Einträge können den Releasenotes zur 1479m entnommen werden.

Zitat

Because almost everything was changed, improved, re-factored and bug-fixed since last release, here are highlighted the most important ones for the end-user:

Start-up HotKeys

=====

'Function' | 'Shortcut' | 'Notes'

=====|=====|=====

Disable Ozmosis | Escape | Press at start-up, screen will flash red to indicate Ozmosis is disabled.

Reset NVRAM | Option+Command+P+R | From F12 menu, Ozmosis GUI, Shell or BIOS Setup.

Start Ozmosis GUI | Option/Home | It can be controlled with mouse only for now.

Safe Boot Mode | Shift |

Verbose Mode | Command+V |

Single-User Mode | Command+S |

32 Bit Boot Mode | 3+2 | Start Up In 32 Bit Mode

64 Bit Boot Mode | 6+4 | Start Up In 64 Bit Mode

Mac/PC Keyboard Legend

=====

'Mac' Key | 'PC' Key

Option | Alt

Command | WinLogo

Added the ability to control graphics and audio injection using NVRAM variables, complete list of variables:

Default Settings 1F8E0C02-58A9-4E34-AE22-2B63745FA101

=====

'Key' | 'Value' | 'Note/Example'

=====|=====|=====

- AcpiLoaderMode | INTEGER | Control ACPI Loader
- UserInterface | BOOLEAN | Display User Interface/GUI
- TimeOut | INTEGER | Time-out In Seconds
- DisableAtiInjection | BOOLEAN | De/activate ATI GFX device property injection
- AtiFramebuffer | STRING | Name of the specific ATI framebuffer
- DisableNvidiaInjection | BOOLEAN | De/activate Nvidia GFX device property injection
- DisableIntelInjection | BOOLEAN | De/activate Intel GFX device property injection
- DisableVoodooHda | BOOLEAN | Disables loading VoodooHDA from firmware
- EnableVoodooHdaInternalSpdif | BOOLEAN | Enable/Disable onboard S/PDIF header when using VoodooHDA from firmware
- DisableBootEntriesFilter | BOOLEAN | Disables filtering of firmware generated boot entries
- AAPL,snb_platform_id | INTEGER |
- AAPL,ig-platform-id | INTEGER |
- BootEntryTemplate | STRING | \$label \$guid
- DarwinDiskTemplate | STRING | \$label \$platform \$major \$minor \$build
- DarwinRecoveryDiskTemplate | STRING | \$label \$platform \$major \$minor \$build

Examples:

=====

!! Note on VoodooHDA, it covers ONLY the onboard codec and is enabled for the moment only for ALC892/ALC1150 !!

!! For discrete graphics HDMI/DP audio AppleHDA is used instead. Those who use internal GPU (IGPU) only will !!

!! have to disable VoodooHda and use AppleHda for HDMI/DP audio !!

To Disable loading VoodooHda.kext from Firmware

```
sudo nvram 1F8E0C02-58A9-4E34-AE22-2B63745FA101:DisableVoodooHda=%01
```

To Enable loading VoodooHda.kext from Firmware

```
sudo nvram 1F8E0C02-58A9-4E34-AE22-2B63745FA101:DisableVoodooHda=%00
```

Changing ATI Framebuffers

=====

```
sudo nvram 1F8E0C02-58A9-4E34-AE22-2B63745FA101:AtiFramebuffer=Futomaki
```

Or based on VendorSubsystemId

```
sudo nvram 1F8E0C02-58A9-4E34-AE22-2B63745FA101:AtiFramebuffer10029440=Futomaki
```

Or based on pci addressing

```
sudo nvram 1F8E0C02-58A9-4E34-AE22-2B63745FA101:AtiFramebuffer00.01.00=Futomaki
```

Changing AAPL,ig-platform-id

=====

```
sudo nvram 1F8E0C02-58A9-4E34-AE22-2B63745FA101:AAPL,ig-platform-id=0x01620005
```

Changing AcpiLoader Mode

=====

Add The Following Values Together For Default Acpi Loader Mode

```
ACPI_LOADER_MODE_DISABLE 0x00000000
ACPI_LOADER_MODE_ENABLE 0x00000001
ACPI_LOADER_MODE_DUMP 0x00000002
ACPI_LOADER_MODE_WINDOWS 0x00000008
ACPI_LOADER_MODE_UPDATE_LEGACY 0x00000040
```

```
Default Value : ACPI_LOADER_MODE_ENABLE | ACPI_LOADER_MODE_DARWIN |
ACPI_LOADER_MODE_UPDATE_LEGACY = 0x45
```

To Change

```
sudo nvram 1F8E0C02-58A9-4E34-AE22-2B63745FA101:AcpiLoaderMode=0x45
```

Note: They can also be controlled by using Defaults.plist placed on boot hard-drive efi system partition and path is /EFI/OZ/Defaults.plist, see bellow for example.

WARNING! Defaults.plist will override the one found in firmware and values are used only if variables are not already added.

For example if you want to set BiosVersion using Defaults.plist and was already set by Defaults from Firmware, you will need

to do a 4 finger NVRAM reset or delete the BiosVersion variable from shell, for the new one to be used.

Default Settings Example of Modifications on Defaults.plist

=====

// If AcpiLoaderMode NEEDS to be changed, change second line, put desired value, then add both line in Defaults.plist

```
<key>AcpiLoaderMode</key>  
<integer>0x45</integer>
```

// If UserInterface NEEDS to be enabled on every boot, change second line and set to true, then add both line in Defaults.plist

```
<key>UserInterface</key>  
<false/>
```

// If TimeOut NEEDS to be changed, change second line and put desired value in seconds, then add both line in Defaults.plist

```
<key>TimeOut</key>  
<integer>5</integer>
```

// If DisableAtiInjection NEEDS to be enabled, change second line bellow and set to true, then add both line in Defaults.plist

```
<key>DisableAtiInjection</key>  
<false/>
```

// If AtiFramebuffer NEEDS to be changed, modify second line bellow and set to correct one, then add both line in Defaults.plist

```
<key>AtiFramebuffer</key>  
<string>ReplaceMe</string>
```

!! WARNING DisableAtiInjection needs to be set to false to function !!

// If DisableNvidiaInjection NEEDS to be enabled, change second line bellow and set to true, then add both line in Defaults.plist

```
<key>DisableNvidiaInjection</key>  
<false/>
```

// If DisableIntelInjection NEEDS to be enabled, change second line bellow and set to true, then add both line in Defaults.plist

```
<key>DisableIntelInjection</key>  
<false/>
```

// If AAPL,snb_platform_id NEEDS to be changed, change second line bellow and set to correct one, then add both line in Defaults.plist

```
<key>AAPL,snb_platform_id</key>  
<integer>0x00030010</integer>
```

!! WARNING DisableIntelInjection needs to be set to false to function !!

// If AAPL,ig-platform-id NEEDS to be changed, modify second line bellow and set to correct one, then add both line in Defaults.plist

```
<key>AAPL,ig-platform-id</key>  
<integer>0x0166000A</integer>
```

!! WARNING DisableIntelInjection needs to be set to false to function !!

// If DisableVoodooHda NEEDS to be enabled, change second line bellow and set to true, then add both line in Defaults.plist

```
<key>DisableVoodooHda</key>  
<false/>
```

// If EnableVoodooHdaInternalSpdif NEEDS to be enabled, change second line bellow and set to true, then add both line in Defaults.plist

```
<key>EnableVoodooHdaInternalSpdif</key>  
<false/>
```

!! WARNING DisableVoodooHda needs to be set to false to function !!

// If DisableBootEntriesFilter NEEDS to be enabled, change second line bellow and set to true, then add both line in Defaults.plist

```
<key>DisableBootEntriesFilter</key>  
<false/>
```

Alles anzeigen

Wie die SMBIOS Werte korrekt gesetzt werden kann dem folgenden Post entnommen werden:
<https://www.hackintosh-forum.de/jeder-Rechner-ein-Unikat/>