

Erledigt

# macOS Sierra - Installationen & Erfahrungsberichte

Beitrag von „Schorse“ vom 13. September 2016, 16:16

Boot nur im Savemode möglich und bei dieser Meldung bleibt es dann auch...  
Was habe ich übersehen?

```
100021] interface: (subscription or this object fetched by line) failed to add subscription for group Intel
RtPort_Broadcom_P2PInterface::configSubscriptions() failed to add subscription
RtPort_Broadcom_P2PInterface::init() role 1
RtPort_Broadcom_P2PInterface::init() role 4
RtPort_Broadcom_P2PInterface::attach() role 4 successful attach to lgt type 147
100021] VirtualInterface::init_controller is (bciffc767091534), provider is (bciffc767091534)
Creating all peerManager reporters
RtPort_Broadcom_P2PInterface::init() role 4
swi0: promiscuous mode enable succeeded
RtPort: Link up on swi0
swi: channel changed to 1
swi0: promiscuous mode disable succeeded
Setting iBMCx Profile: band0
Profile01: mode:0; device:0; device_level:0; chain_power_offset:0,0,0,0
Profile02: mode:0; device:0; device_level:1; chain_power_offset:-7,0,-7,0
Profile03: mode:0; device:1; device_level:1; chain_power_offset:-7,0,-7,0
RtPort: 4:000000: w0: setDMA_PEER_TRAFFIC_REGISTRATION: active 0, ram_off: 0, ser 0 ram_start_set 0 Force
swi0: promiscuous mode enable succeeded
Setting iBMCx Profile: band2
Profile01: mode:0; device:0; device_level:0; chain_power_offset:0,0,0,0
Setting iBMCx Config: enable_2G:1, profile_2g:0, enable_5G:1, profile_5G:0
Setting iBMCx Config: enable_2G:1, profile_2g:0, enable_5G:1, profile_5G:0
Ethernet (Hithers2200): Link up on swi, 1-Gigabit, full-duplex, 80/15 flow-control
swi: 002:1fd country code set to 'DE'
swi: Supported channels 1 2 3 4 5 6 7 8 9 10 11 12 13 36 40 44 48 52 56 60 64 100 104 108 112 116 120 124 128
AppleRTC: patcher 0 backup patching applied only to patches out of 20
SanDiskValidation: (trp0fd72) deny() File-read-metadata /Library/Preferences/com.apple.security.osmss.plist
SanDiskValidation: (cfbackd111) System Policy: allow() File-Local /dev/tr0ad02
SanDiskValidation: (rpn0cd112) deny() web-backup com.apple.metadata.edu.library
busy timeout(0), (004), kexd wait(0): 'IDERCCodeFunction', 'AppleOS2000ofApple', 'IDERCCodeFunction'
Stealth Mode connection attempt to IP: 192.168.178.38:80 From 192.168.178.1:43737
Stealth Mode connection attempt to IP: 192.168.178.38:80 From 192.168.178.1:43737
busy timeout(1), (004), kexd wait(0): 'IDERCCodeFunction', 'AppleOS2000ofApple', 'IDERCCodeFunction'

```