

**Erledigt**

## Fehlermeldung in der bdmesg trotz DSDT für HP XW4600

Beitrag von „janblohm“ vom 3. September 2012, 21:51

Hallo nachdem ich nun seit einiger Zeit relativ Problemlos mit der hier durch das Forum erstellten DSDT <http://www.hackintosh-forum.de...ighlight=xw4600#post25581> gearbeitet habe ist mir bei der Durchsicht der bdmesg auf gefallen, dass hier Fehlermedlungen ausgegeben werden. Es wäre schön, wenn sich das einmal jemand anschauen kann, der mit diesem Gebiet sehr viel mehr Erfahrung hat. Vielleicht habt Ihr ja auch einen Lösungsvorschlag. Der Hauptfehler scheint bei der Generierung der P- und C-States zu liegen, oder?

Vielen Dank 😞

Chameleon 2.1svn (svn-r2033) [2012-08-03 14:18:47]

msr(447): ia32\_perf\_stat 0x06004822

max: 8.5 current: 8.5

CPU: Brand String: Intel(R) Core(TM)2 Quad CPU Q9550 @ 2.83GHz

CPU: Vendor/Family/ExtFamily: 0x756e6547/0x6/0x0

CPU: Model/ExtModel/Stepping: 0x17/0x1/0xa

CPU: MaxCoef/CurrCoef: 0x8/0x8

CPU: MaxDiv/CurrDiv: 0x1/0x1

CPU: TSCFreq: 2833MHz

CPU: FSBFreq: 333MHz

CPU: CPUFreq: 2833MHz

CPU: NoCores/NoThreads: 4/4

CPU: Features: 0x0000025f

Attempting to read GPT

Read GPT

Reading GPT partition 1, type C12A7328-F81F-11D2-BA4B-00A0C93EC93B

Reading GPT partition 2, type 48465300-0000-11AA-AA11-00306543ECAC

Reading GPT partition 3, type 48465300-0000-11AA-AA11-00306543ECAC

Reading GPT partition 4, type 48465300-0000-11AA-AA11-00306543ECAC

Read HFS+ file: [hd(0,3)/System/Library/CoreServices/SystemVersion.plist] 478 bytes.

Read HFS+ file: [hd(0,2)/System/Library/CoreServices/SystemVersion.plist] 478 bytes.

Read HFS+ file: [hd(0,2)/Extra/org.chameleon.Boot.plist] 776 bytes.  
Read HFS+ file: [hd(1,2)/System/Library/CoreServices/SystemVersion.plist] 478 bytes.  
Module 'Symbols.dylib' by 'Chameleon' Loaded.

Read HFS+ file: [hd(0,2)/Library/Preferences/SystemConfiguration/com.apple.Boot.plist] 232 bytes.

Read HFS+ file: [hd(0,2)/Extra/org.chameleon.Boot.plist] 776 bytes.

Loading Darwin 10.7

Loading kernel cache /System/Library/Caches/com.apple.kext.caches/Startup/kernelcache

Read HFS+ file: [hd(0,2)/System/Library/Caches/com.apple.kext.caches/Startup/kernelcache] 4096 bytes.

Read HFS+ file: [hd(0,2)/System/Library/Caches/com.apple.kext.caches/Startup/kernelcache] 13760450 bytes.

Using PCI-Root-UID value: 1

Read HFS+ file: [hd(0,2)/Extra/smbios.plist] 955 bytes.

Intel X38/X48 DRAM Controller [8086:29e0] at 00:00.0

Frequency detected: 400 MHz (800) Dual Channel

CAS:6 tRC:6 tRP:6 RAS:18 (6-6-6-18)

SMBus CmdReg: 0x1

Scanning SMBus [8086:2930], mmio: 0xf0305004, ioport: 0xfc00, hostc: 0x1

SPD[0] (size): 128 @0x50

Slot: 0 Type 19 2048MB (DDR2 SDRAM) 800MHz Vendor=Samsung

PartNo=M391T5663QZ3-CF73Q SerialNo=8399A3F7

SPD[0] (size): 128 @0x51

Slot: 1 Type 19 2048MB (DDR2 SDRAM) 800MHz Vendor=Samsung

PartNo=M391T5663QZ3-CF73Q SerialNo=8399A298

SPD[0] (size): 128 @0x52

Slot: 2 Type 19 2048MB (DDR2 SDRAM) 800MHz Vendor=Samsung

PartNo=M391T5663QZ3-CF73Q SerialNo=8399A2A3

SPD[0] (size): 128 @0x53

Slot: 3 Type 19 2048MB (DDR2 SDRAM) 800MHz Vendor=Samsung

PartNo=M391T5663QZ3-CF73Q SerialNo=8399A2A8

SPD[0] (size): 255 @0x54

SPD[0] (size): 255 @0x55

SPD[0] (size): 255 @0x56

SPD[0] (size): 255 @0x57

CPU is Intel(R) Core(TM)2 Quad CPU Q9550 @ 2.83GHz, family 0x6, model 0x17

Type: 0, Length: 24, Handle: 0x1

BIOSInformation:

vendor: Apple Computer, Inc.

version: MP31.88Z.006C.B05.0802291410

releaseDate: 02/29/08

Type: 1, Length: 27, Handle: 0x2

SystemInformation:

manufacturer: Apple Computer, Inc.

productName: MacPro3,1

version: 1.0

serialNumber: CK935356XYL

uuid: 635AD1B4-43F4-DD11-BBD8-7D1BBAEC0023

wakeupReason: 0x6

skuNumber: RV724AV

family: Mac Pro

Type: 2, Length: 14, Handle: 0x3

BaseBoard:

manufacturer: Apple Inc.

product: Mac-F42C88C8

version: -õ

serialNumber: CZC9053X01

assetTagNumber: Jans Workstation

locationInChassis: -õ

boardType: 0xA

Type: 3, Length: 17, Handle: 0x4

SystemEnclosure:

manufacturer: Hewlett-Packard

type: 134

version: -õ

serialNumber: CZC9053X01

assetTagNumber: Jans Workstation

Type: 4, Length: 40, Handle: 0x5

ProcessorInformation:

socketDesignation: XU1 PROCESSOR

processorType: 3

processorFamily: 0xB2

manufacturer: Intel

processorID: 0x1067A

processorVersion: Intel(R) Core(TM)2 Quad CPU Q9550 @ 2.83GHz  
externalClock: 333MHz  
maximumClock: 2833MHz  
currentClock: 2833MHz  
serialNumber: -  
assetTag: -  
partNumber: -

MemoryDevice:  
deviceLocator: XMM1  
bankLocator: -  
memoryType: DDR2 SDRAM  
memorySpeed: 800MHz  
manufacturer: Samsung  
serialNumber: 8399A3F7  
assetTag: -  
partNumber: M391T5663QZ3-CF73Q

Type: 17, Length: 27, Handle: 0x3d  
MemoryDevice:  
deviceLocator: XMM2  
bankLocator: -  
memoryType: DDR2 SDRAM  
memorySpeed: 800MHz  
manufacturer: Samsung  
serialNumber: 8399A298  
assetTag: -  
partNumber: M391T5663QZ3-CF73Q

Type: 17, Length: 27, Handle: 0x3e  
MemoryDevice:  
deviceLocator: XMM3  
bankLocator: -  
memoryType: DDR2 SDRAM  
memorySpeed: 800MHz  
manufacturer: Samsung  
serialNumber: 8399A2A3  
assetTag: -

partNumber: M391T5663QZ3-CF73Q

Type: 17, Length: 27, Handle: 0x3f

MemoryDevice:

deviceLocator: XMM4

bankLocator: -õ

memoryType: DDR2 SDRAM

memorySpeed: 800MHz

manufacturer: Samsung

serialNumber: 8399A2A8

assetTag: -õ

partNumber: M391T5663QZ3-CF73Q

Type: 17, Length: 27, Handle: 0x41

MemoryDevice:

deviceLocator: SYSTEM ROM

bankLocator: -õ

memoryType: DDR2 SDRAM

memorySpeed: 800MHz

manufacturer: N/A

serialNumber: N/A

assetTag: -õ

partNumber: N/A

AppleProcessorType:

ProcessorType: 0x501

Type: 127, Length: 4, Handle: 0x55

Customizing SystemID with : 635ad1b4-43f4-dd11-bbd8-7d1bbaec0023

efi\_inject\_get\_devprop\_string NULL trying stringdata

Read HFS+ file: [hd(0,2)/Extra/DSDT.aml] 37230 bytes.

ACPI table not found: SSDT.aml

FADT: changing PM\_Profile from 0x00 to 0x03

FADT: ACPI Restart Fix applied!

FADT: Using custom DSDT!

Invalid character found in ProcessorOP 0x2e!

Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0xffffffff0!  
ACPI CPUs not found: C-States not generated !!!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0xffffffff0!  
ACPI CPUs not found: P-States not generated !!!  
FADT: ACPI Restart Fix applied!  
FADT: Using custom DSDT!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0xffffffff0!  
ACPI CPUs not found: C-States not generated !!!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0x2e!  
Invalid character found in ProcessorOP 0xffffffff0!  
ACPI CPUs not found: P-States not generated !!!  
Starting Darwin x86\_64  
Boot Args: boot-uuid=AA54655A-9822-3B88-AB3E-135C3BF63237 rd=\*uuid  
UseKernelCache=Yes -v