

Erledigt **Snow Leopard instalation**

Beitrag von „ps3fan90“ vom 8. September 2012, 16:43

```
npvhash=4095
PHE enabled
rtclock_init: Taking bus ratio path 4 (Intel / Apple)
TSC: Verification of clock speed PASSED.
TSC: Frequency = 2671.752000MHz, FSB frequency = 333.969000MHz, bus
Darwin Kernel Version 10.0.0: Thu Oct 28 09:24:50 EDT 2010; root:xnu-160.0.0/~/
via_page_bootstrap: 962796 free pages and 85780 wired pages
standard timeslicing quantum is 10000 us
mig_table_max_displ = 73
warning: skipping personalities in blacklisted kext com.apple.driver.F
NullCPUPowerManagement::init: properties=0x8dd2a80
NullCPUPowerManagement::start
AppleACPICPU: ProcessorId=1 LocalApicId=0 Enabled
AppleACPICPU: ProcessorId=2 LocalApicId=1 Enabled
AppleACPICPU: ProcessorId=3 LocalApicId=130 Disabled
AppleACPICPU: ProcessorId=4 LocalApicId=131 Disabled
calling mpo_policy_init for Quarantine
Security policy loaded: Quarantine policy (Quarantine)
calling mpo_policy_init for Sandbox
Security policy loaded: Seatbelt sandbox policy (Sandbox)
calling mpo_policy_init for TMSafetyNet
Security policy loaded: Safety net for Time Machine (TMSafetyNet)
Copyright (c) 1982, 1986, 1989, 1991, 1993
The Regents of the University of California. All rights reserved.

MRC Framework successfully initialized
using 16384 buffer headers and 4896 cluster ID buffer headers
IOAPIC: Version 0x20 Vectors 64:87
ACPI: System State [S0 S3 S4 S5] (S3)
RTC: Only single RAM bank (128 bytes)
netkas presents fakesmc, a kext which emulates smc device
mbinit: done (64 MB memory set for mbuf pool)
Added memory device md0/rmd0 (02000000/0A000000) at 01006000 for 027000
From path: "uuld",
Waiting for boot volume with UUID 0396BD91-CD39-3768-845F-955AE3617C92
Waiting on <dict ID="0"><key>IOProviderClass</key><string ID="1">IOReso
ot-uuld-media</string></dict>
com.apple.AppleFSCompressionTypeZlib load succeeded
Identified as RTL8168B/8111B
Still waiting for root device
█
```

Gesendet von mein iPhone 3Gs (OldBootROM) mit Jailbreack via Tapatalk