

Erledigt

AppleALC ins BIOS

Beitrag von „Skorpi08“ vom 22. Januar 2018, 22:29

Code

1. p.p1 {margin: 0.0px 0.0px 0.0px 0.0px; font: 11.0px Menlo; color: #000000; background-color: #ffffff}
2. span.s1 {font-variant-ligatures: no-common-ligatures}
- 3.
- 4.
5. 38 1 0xffffffff7f824fb000 0x19000 0x19000 as.vit9696.Lilu (1.2.2) B43828BB-6A20-3D60-AF53-C2FEE9FE0850 <7 5 4 3 2 1>
- 6.
- 7.
8. 39 3 0xffffffff7f82514000 0x11000 0x11000 org.netkas.driver.FakeSMC (1765) 9EEC6103-EEBA-34B3-B9AF-8FE333C43E90 <11 7 5 4 3 1>
- 9.
- 10.
11. 40 0 0xffffffff7f82525000 0xca000 0xca000 as.vit9696.AppleALC (1.2.2) C581E250-A491-3949-93D7-1EFBF529898F <38 7 5 4 3 2 1>
- 12.
- 13.
14. 41 0 0xffffffff7f825ef000 0x5000 0x5000 org.hwsensors.driver.CPUSensors (1765) AB5DE333-8AC8-3549-86E5-C5647AACA61F <39 7 5 4 3>
- 15.
- 16.
17. 54 0 0xffffffff7f825f5000 0x8000 0x8000 org.hwsensors.driver.ACPI Sensors (1765) FA4DF6C0-0D3A-3CE2-8569-0AB2C84053E7 <39 11 7 5 4 3>
- 18.
- 19.
20. 59 0 0xffffffff7f825ff000 0x14000 0x14000 com.insanelymac.IntelMausiEthernet (2.3.0) 7664CC46-C3FE-3D04-93EE-FC1E4EFBBFB7 <16 12 5 4 3 1>
- 21.
- 22.
23. 64 0 0xffffffff7f82617000 0xd000 0xd000 org.hwsensors.driver.LPCSensors (1765) 93417250-FFB4-39DA-8B25-F164DE72E120 <39 12 11 7 5 4 3>

Alles anzeigen