

Erledigt

OS X High Sierra installieren nach vorhandener OS X Mojave Installation

Beitrag von „Blu“ vom 8. Mai 2019, 21:33

Ich verstehe nicht was da falsch ist, habe die optimalste Hardware aber er will irgendwie nicht



Egal was ich probiere, auch wenn ich von der SSD boote, er geht nie weiter als so:

```
RCPI Error: Method parse/executation failed (X) (code 11111111/0000/0000, 1-5-1017/0000/0000)
RCPI: Executed 55 blocks of module-level executable ARM code
RCPI: sleep states 53 54 55
pci (build 20:47:59 Mar 11 2019), flags 0x20:3000
HID: Legacy shia 2
HID: Legacy shia 2
[ PCI configuration begin ]
console relocated to 0x7f00000000
[ PCI configuration end, bridges 5, devices 13 ]
SMCChipID: main 0 detected device hardware MC167960
000002.505241 AppleASLLegacyHost: AppleASLLegacyHost::init: enabling legacy matching
Copyright (c) 1982, 1985, 1989, 1991, 1993
The Regents of the University of California. All rights reserved.
000002.002590 AppleASLHost: AppleASLHost::createPorts: unsupported speed unitless 1248 exponent 2

MFC Framework successfully initialized
using 16384 buffer headers and 16240 cluster 10 buffer headers
cache: 6 CPU(s), 64 bytes CPU cache line size
shlib: done (128 MB total pool size, 05/02) sp(1)
000002.012020 AppleASLHost: AppleASLHost::createPorts: unsupported speed unitless 2496 exponent 2
com.apple.AppleASLCompressionTypeZlib load start
com.apple.AppleASLCompressionTypeZlib load start
calling spa_policy_init for ASP
000002.044181 AppleASLHost: AppleASLHost::createPorts: unsupported speed unitless 4992 exponent 2
000002.044205 AppleASLHost: AppleASLHost::createPorts: unsupported speed unitless 1457 exponent 2
000002.044419 AppleASLHost: AppleASLHost::createPorts: unsupported speed unitless 2315 exponent 2
000002.044625 AppleASLHost: AppleASLHost::createPorts: unsupported speed unitless 5638 exponent 2
000002.045425 AppleASLHost: AppleASLHost::createPorts: ports limit reached. Not creating the remaining 11 ports
Security policy loaded: Apple System Policy (ASP)
com.apple.AppleASLCompressionTypeZlib load succeeded
com.apple.AppleASLCompressionTypeZlib load succeeded
waiting via host-uid from /chassis: 4120419:5931-430-80C-C700071267
000002.131847 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 150 sleepbits 0
000002.202277 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 150 sleepbits 0
000002.213398 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 150 sleepbits 0
000002.224330 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 150 sleepbits 0
000002.235166 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 150 sleepbits 0
000002.245985 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 150 sleepbits 0
000002.256597 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 150 sleepbits 0
000002.267224 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 100 sleepbits 0
000002.277784 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 100 sleepbits 0
000002.288219 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 100 sleepbits 0
000002.298701 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 100 sleepbits 0
000002.309475 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 100 sleepbits 0
000002.318343 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 100 sleepbits 0
000002.328142 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 300 sleepbits 0
000002.337660 AppleASLHostResources: AppleASLHostResources::interruptOccurred: clearing change bits on smed part 24 with portID 0x02e0
000002.336444 AppleASLHostResources: AppleASLHostResources::interruptOccurred: clearing change bits on smed part 24 with portID 0x02e0
000002.346256 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 300 sleepbits 0
000002.356012 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 150 sleepbits 0
USBC: Identifier (non-unique): 071388:2C2E438 Bx1b0 Bx243 Bx110, 2
000002.624313 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 300 sleepbits 0
000002.693694 AppleASLHostResources: AppleASLHostResources::all locateDownstreamCurrentGated: assessing successful wdsbits 300 sleepbits 0
HID: Legacy shia 2
vfs_ashlib_start:1393: load: com.apple.filesystems.apfs, v95.250.134, apfs-945.250.134, 2019/03/11
```