

Erledigt Hackintosh 2019

Beitrag von „Schrolli“ vom 1. August 2019, 17:31

Hmm da passt noch was nicht.

```
libser/macros: value (value: 0x0), file: /BuildRoot/Library/Caches/com.apple.xbs/Sources/AppleCredentialManager/AppleCredentialManager-226.270.1/AppleCredentialManager/AppleCredentialManager
ACPI: SSDT 0x00000000E701000 0014E2 (v02 ALASKA TbtTypeC 00000000 INTL 20160527)
ACPI: DGP 0x00000000EBC95E0 000034 (v01 ALASKA A M I 00000002 01000013)
ACPI: DGG2 0x00000000EBC9610 000054 (v00 ALASKA A M I 00000002 01000013)
ACPI: SSDT 0x00000000EBC9F000 001067 (v02 ALASKA UsbCtbl 00001000 INTL 20160527)
ACPI: AppleCredentialManager: Init: EOS device type: 0.
ACM: InitCredentialEngine: Global credential set created, CSI10.
AppleCredentialManager: Init: returning, result = true, instance = <ptr>.
SSDT 0x00000000EBC900 000144 (v02 Intel ADabTbl 00001000 INTL 20160527)
ACPI: BGR1 0x00000000EBC9300 000030 (v01 ALASKA A M I 01072009 AMI 00010013)
ACPI: USMT 0x00000000EBC9300 000028 (v01 ALASKA A M I 01072009 AMI 00010013)
AppleCredentialManager: start: called, instance = <ptr>.
AppleCredentialManager: start: started, instance = <ptr>.
AppleCredentialManager: start: returning, result = true, instance = <ptr>.
AppleKeyStore starting (BUILT: Jun 23 2019 21:45:22)
AppleKeyStore::start: _kernel_relay_enable = 0
AppleKeyStore::start: _sep_enabled = 0
USBInjectAll: utl_include specifies "HS01,HS03,HS05,HS07,HS09,HS11,HS13"
USBInjectAll: utl_exclude specifies "HS01,HS02,HS03,HS04,HS05,HS06,HS07,HS08,HS09,HS10,HS11,HS12,HS13,HS14"
ACPI: 9 ACPI AML tables successfully acquired and loaded
AppleACPICPU: ProcessorId=1 LocalApicId=0 Enabled
AppleACPICPU: ProcessorId=2 LocalApicId=2 Enabled
AppleACPICPU: ProcessorId=3 LocalApicId=4 Enabled
AppleACPICPU: ProcessorId=4 LocalApicId=6 Enabled
AppleACPICPU: ProcessorId=5 LocalApicId=8 Enabled
AppleACPICPU: ProcessorId=6 LocalApicId=10 Enabled
AppleACPICPU: ProcessorId=7 LocalApicId=12 Enabled
AppleACPICPU: ProcessorId=8 LocalApicId=14 Enabled
AppleACPICPU: ProcessorId=9 LocalApicId=1 Enabled
AppleACPICPU: ProcessorId=10 LocalApicId=3 Enabled
AppleACPICPU: ProcessorId=11 LocalApicId=5 Enabled
AppleACPICPU: ProcessorId=12 LocalApicId=7 Enabled
AppleACPICPU: ProcessorId=13 LocalApicId=9 Enabled
AppleACPICPU: ProcessorId=14 LocalApicId=11 Enabled
AppleACPICPU: ProcessorId=15 LocalApicId=13 Enabled
AppleACPICPU: ProcessorId=16 LocalApicId=15 Enabled
calling apm_policy_init for RRF1
Security policy loaded: Apple Mobile File Integrity (AMFI)
calling apm_policy_init for Sandbox
Security policy loaded: Smartbelt sandbox policy (Sandbox)
calling apm_policy_init for Quarantine
Security policy loaded: Quarantine policy (Quarantine)
calling apm_policy_init for TMSafetyNet
Security policy loaded: Safety net for Time Machine (TMSafetyNet)
IDPFIC: Version 0x20 Vectors 0x111
ACPI: Executed 43 blocks of mobile-level executable AML code
ACPI: sleep states S3 S4 S5
pci (build 10:51:57 Jun 20 2019), flags 0x20c3000
HID: Legacy shia 2
SHRCT: start
HID: Legacy shia 2
[ PCI configuration begin ]
console relocated to 0x7f8000000
[ PCI configuration end. Bridges 13, devices 10 ]
getFeatures() ==>
AppleNvme Assert failed: ( 0 != data ) getFeatures() <==
AirPort_BrcmNIC::Init AirPortFamily_kexts-1437.3 "AirPortFamily_kexts-1437.3" Jun 20 2019 19:11:41
IOPCIDevice file: /BuildRoot/Library/Caches/com.apple.xbs/Sources/IOPCIDevice/IOPCIDevice-307.270.1/IOPCIDeviceController.cpp line: 9492
virtual IOReturn IOHwController::CreateSubmissionQueue(uint16_t, uint8_t):2704:SQ index=0 entrysize=64
RRPT: 1-262700: AirPort_Brcm300:probe, this[0x7f8000000] score[2048]
AirPort_Brcm300::Init AirPortFamily_kexts-1437.3 "AirPortFamily_kexts-1437.3" Jun 20 2019 19:11:41
RRPT: 1-263043: AirPort_Brcm300:probe, this[0x7f8000000] score[1110]
SHCSeparID: slot 0 detected device Nuvoton NCT6791D
apfs_module_start:1393: load: com.apple.filesystems.apfs, v945.273.7, apfs-945.273.7, 2019/06/23
```