

Erledigt Hackintosh 2019

Beitrag von „Schrolli“ vom 1. August 2019, 19:44

Ne da sagst was. Das mit der iGPU hatte ich sogar schon mal gelesen.

Aber ist auch gerade wieder stehen geblieben.

```
ACPI: SSDT 0x00000000E710000 000378 (v01 SataRe SataTabl 00001000 INTL 20160527)
ACPI: SSDT 0x00000000E700000 0031C6 (v02 SaSadt SaSadt 00003000 INTL 20160527)/fsstMacros: value (value=0x0), file: /BuildRoot/Library/Caches/com.apple.xbs/Sources/AppleCredentialManager/AppleCredentialManager.cpp:57
AppleCredentialManager: Init: EDS device type: 0.
ACPI: InitCredentialManager: Global credential set created, CS(10).
AppleCredentialManager: Init: returning, result = true, instance = <ptr>.
ACPI: SSDT 0x00000000E700000 002310 (v02 PegSadt PegSadt 00001000 INTL 20160527)
ACPI: NPET 0x00000000E700000 000038 (v01 ALASKA A M I 00000002 01000013)
ACPI: SSDT 0x00000000E700000 000144 (v02 INTEL xh_cfsm4 00000000 INTL 20160527)
ACPI: UEFI 0x00000000E700000 000042 (v01 ALASKA A M I 00000002 01000013)
ACPI: LPIT 0x00000000E700000 00005C (v01 ALASKA A M I 00000002 01000013)
AppleCredentialManager: start: started, instance = <ptr>.
AppleCredentialManager: start: returning, result = true, instance = <ptr>.
AppleKeyStore starting (BUILT: Jun 23 2019 21:43:22)
AppleKeyStore::start: _kernel_relay_enable = 0
AppleKeyStore::start: _sep_enabled = 0
ACPI: SSDT 0x00000000E700000 0014E2 (v02 ALASKA TbtTypeC 00000000 INTL 20160527)
ACPI: D0G2 0x00000000E700000 000034 (v01 ALASKA A M I 00000002 01000013)
ACPI: D0G2 0x00000000E700000 000054 (v00 ALASKA A M I 00000002 01000013)
ACPI: SSDT 0x00000000E700000 001067 (v02 ALASKA UabCTabl 00001000 INTL 20160527)
ACPI: BGR1 0x00000000E700000 000038 (v01 Intel AdbCTabl 00001000 INTL 20160527)
ACPI: WSH1 0x00000000E700000 000028 (v01 ALASKA A M I 01072009 AWT 00010013)
ACPI: WSH1 0x00000000E700000 000053 (v01 PaRef CpuPa 00003000 INTL 20120320)
ACPI: 10 ACPI AML tables successfully acquired and loaded
AppleACPICPU: ProcessorId=1 LocalApicId=0 Enabled
AppleACPICPU: ProcessorId=2 LocalApicId=2 Enabled
AppleACPICPU: ProcessorId=3 LocalApicId=4 Enabled
AppleACPICPU: ProcessorId=4 LocalApicId=6 Enabled
AppleACPICPU: ProcessorId=5 LocalApicId=8 Enabled
AppleACPICPU: ProcessorId=6 LocalApicId=10 Enabled
AppleACPICPU: ProcessorId=7 LocalApicId=12 Enabled
AppleACPICPU: ProcessorId=8 LocalApicId=14 Enabled
AppleACPICPU: ProcessorId=9 LocalApicId=1 Enabled
AppleACPICPU: ProcessorId=10 LocalApicId=3 Enabled
AppleACPICPU: ProcessorId=11 LocalApicId=5 Enabled
AppleACPICPU: ProcessorId=12 LocalApicId=7 Enabled
AppleACPICPU: ProcessorId=13 LocalApicId=9 Enabled
AppleACPICPU: ProcessorId=14 LocalApicId=11 Enabled
AppleACPICPU: ProcessorId=15 LocalApicId=13 Enabled
AppleACPICPU: ProcessorId=16 LocalApicId=15 Enabled
calling mpo_policy_init for AFWI
Security policy loaded: Apple Mobile File Integrity (AMFI)
calling mpo_policy_init for Sandbox
Security policy loaded: Seatbelt sandbox policy (Sandbox)
calling mpo_policy_init for Quarantine
Security policy loaded: Quarantine policy (Quarantine)
calling mpo_policy_init for TMSafetyNet
Security policy loaded: Safety net for Time Machine (TMSafetyNet)
IOAPIC: Version 0x20 Vectors 64:111
ACPI: Executed 45 blocks of module-level executable AML code
ACPI: sleep states S3 S4 S5
pci (build 10:51:57 Jun 20 2019), flags 0x20c3000
HID: Legacy shia 2
HID: Legacy shia 2
SHCRT: start
[ PCI configuration begin ]
console relocated to 0x7f0000000
[ PCI configuration end, bridges 13, devices 18 ]
getFeatures() ==>
AppleWwio Assert failed: ( 0 != data ) getFeatures() <==
ReleaseNode file: /BuildRoot/Library/Caches/com.apple.xbs/Sources/IOWwioFamily/IOWwioFamily-397.270.1/IOWwioController.cpp (line: 5492)
virtual IOReturn IOWwioController::CreateSubmissionQueue(uint16_t, uint8_t)::2704:SQ index=9 entrySize=64
virtual IOReturn IOWwioController::CreateSubmissionQueue(uint16_t, uint8_t)::2704:SQ index=1 entrySize=64
```