

# Gigabyte Z390 DESIGNARE: fertiger Clover-EFI-Ordner zum Download

Beitrag von „JimSalabim“ vom 17. Oktober 2019, 13:31

[Floetzing Ignaz](#) Na klar. Diesen Code

Code

```
1. <key>PciRoot(0x0)/Pci(0x2,0x0)</key>
2. <dict>
3. <key>AAPL,ig-platform-id</key>
4. <data>
5. BwCbPg==
6. </data>
7. <key>AAPL,model</key>
8. <string>Intel UHD 630</string>
9. <key>AAPL,slot-name</key>
10. <string>Internal</string>
11. <key>device-id</key>
12. <data>
13. mz4AAA==
14. </data>
15. <key>device_type</key>
16. <string>Graphics Processor</string>
17. <key>enable-hdmi20</key>
18. <data>
19. AQAAAA==
20. </data>
21. <key>framebuffer-con0-busid</key>
22. <data>
23. BQAAAA==
24. </data>
25. <key>framebuffer-con0-enable</key>
26. <data>
27. AQAAAA==
28. </data>
29. <key>framebuffer-con0-flags</key>
30. <data>
31. xwMAAA==
32. </data>
```

33. <key>framebuffer-con0-index</key>  
34. <data>  
35. AQAAAA==  
36. </data>  
37. <key>framebuffer-con0-pipe</key>  
38. <data>  
39. EgAAAA==  
40. </data>  
41. <key>framebuffer-con0-type</key>  
42. <data>  
43. AAQAAA==  
44. </data>  
45. <key>framebuffer-con1-busid</key>  
46. <data>  
47. BgAAAA==  
48. </data>  
49. <key>framebuffer-con1-enable</key>  
50. <data>  
51. AQAAAA==  
52. </data>  
53. <key>framebuffer-con1-flags</key>  
54. <data>  
55. xwMAAA==  
56. </data>  
57. <key>framebuffer-con1-index</key>  
58. <data>  
59. AgAAAA==  
60. </data>  
61. <key>framebuffer-con1-pipe</key>  
62. <data>  
63. EgAAAA==  
64. </data>  
65. <key>framebuffer-con1-type</key>  
66. <data>  
67. AAQAAA==  
68. </data>  
69. <key>framebuffer-con2-busid</key>  
70. <data>  
71. BAAAAA==  
72. </data>  
73. <key>framebuffer-con2-enable</key>  
74. <data>  
75. AQAAAA==

76. </data>  
77. <key>framebuffer-con2-flags</key>  
78. <data>  
79. xwMAAA==  
80. </data>  
81. <key>framebuffer-con2-index</key>  
82. <data>  
83. AwAAAA==  
84. </data>  
85. <key>framebuffer-con2-pipe</key>  
86. <data>  
87. EgAAAA==  
88. </data>  
89. <key>framebuffer-con2-type</key>  
90. <data>  
91. AAgAAA==  
92. </data>  
93. <key>framebuffer-con3-busid</key>  
94. <data>  
95. AAAAAA==  
96. </data>  
97. <key>framebuffer-con3-enable</key>  
98. <data>  
99. AQAAAA==  
100. </data>  
101. <key>framebuffer-con3-flags</key>  
102. <data>  
103. IAAAAA==  
104. </data>  
105. <key>framebuffer-con3-index</key>  
106. <data>  
107. /////w==  
108. </data>  
109. <key>framebuffer-con3-pipe</key>  
110. <data>  
111. AAAAAA==  
112. </data>  
113. <key>framebuffer-con3-type</key>  
114. <data>  
115. AQAAAA==  
116. </data>  
117. <key>framebuffer-patch-enable</key>  
118. <data>

119. AQAAAA==
120. </data>
121. </dict>

Alles anzeigen

mit diesem ersetzen:

Code

1. <key>PciRoot(0x0)/Pci(0x2,0x0)</key>
2. <dict>
3. <key>AAPL,ig-platform-id</key>
4. <data>
5. AwCYPg==
6. </data>
7. <key>AAPL,slot-name</key>
8. <string>Internal@0,2,0</string>
9. <key>device\_type</key>
10. <string>Display controller</string>
11. <key>framebuffer-patch-enable</key>
12. <data>
13. AQAAAA==
14. </data>
15. <key>hda-gfx</key>
16. <string>onboard-2</string>
17. <key>model</key>
18. <string>Intel UHD Graphics 630 (Desktop 9 Series)</string>
19. </dict>

Alles anzeigen