

Erledigt

Neubau Hackintosh "MSI MPG Z390 GAMING PLUS Intel Z390" mit "Intel Core i7 9700" und "Sapphire AMD Radeon RX 560 Pulse"

Beitrag von „anonymous_writer“ vom 18. November 2019, 20:43

Freut mich das es jetzt läuft. 🍷🍷

ExposeSensitiveData habe ich auf 3. Sollte aber egal sein.

```
2. ExposeSensitiveData
Type: plist integer
Fallback: 0x6
Description: Sensitive data exposure bitmask (sum) to operating system.
  • 0x01 — Expose printable booter path as an UEFI variable.
  • 0x02 — Expose OpenCore version as an UEFI variable.
  • 0x04 — Expose OpenCore version in boot picker menu title.

Exposed booter path points to OpenCore.efi or its booter depending on the load order. To obtain booter path
use the following command in macOS:

$nvram 4D1FDA02-38C7-4A6A-9CC6-480CC81B30102:boot-path

To use booter path for mounting booter volume use the following command in macOS:

v=$(nvram 4D1FDA02-38C7-4A6A-9CC6-480CC81B30102:boot-path | sed 's/.*GPT,\([^\,]*\),.*$/\1/'); \
if [ "$v" != "" ]; then sudo diskutil mount $v ; fi

To obtain OpenCore version use the following command in macOS:

$nvram 4D1FDA02-38C7-4A6A-9CC6-480CC81B30102:opencore-version
```