

Alienware m15 R1 - Dual GPU Gaming Notebook - lauffähige Konfiguration (EFI inside)

Beitrag von „elmacci“ vom 3. Dezember 2019, 21:48

Hi,

it seems like you have appleps2smarttouchpad AND VoodooI2C/VoodooCHID Kext in the kext folder, maybe in /other and /10.15.? Dont use both at the same time.

There are 2 possible ways to get the trackpad and keyboard working.

1) Only use ApplePS2Smartatouchpad Kext

2) Use VoodooI2C and VoodooCHID together with SSDT-XOSI.aml and Rename _OSI to XOSI patch for the Trackpad and VoodooPs2controller kext for the keyboard. Additional Info: You should open the voodoops2controller via right click in finder and „show content of package“ and delete the mouse and trackpad part in the folder plugins, as voodooi2c takes care of the touchpad and this way both kexts dont interfere with each other.

All of this is btw necessary because the Alienware m15 uses I2C for the Trackpad and Ps2 for the keyboard hardwarewise.

Although i included ApplePs2Smarttouchpad in my efi here, I recommend method 2) if you dont mind the extra trouble. Much smoother trackpad experience with functioning multi gestures, but a little more complicated.

cheers

EDIT: I updated my first post and included the optimized EFI V2