

Catalina Installation Bootvorgang Pausing 5 secs...

Beitrag von „ucode“ vom 27. Januar 2020, 20:29

Einen Schritt weiter zumindest

```
AppleACPICPU: ProcessorId=4 LocalApicId=6 Enabled
AppleACPICPU: ProcessorId=5 LocalApicId=9 Enabled
AppleACPICPU: ProcessorId=6 LocalApicId=10 Enabled
AppleACPICPU: ProcessorId=7 LocalApicId=1 Enabled
AppleACPICPU: ProcessorId=8 LocalApicId=3 Enabled
AppleACPICPU: ProcessorId=9 LocalApicId=5 Enabled
AppleACPICPU: ProcessorId=10 LocalApicId=7 Enabled
AppleACPICPU: ProcessorId=11 LocalApicId=9 Enabled
AppleACPICPU: ProcessorId=12 LocalApicId=11 Enabled
calling smp_policy_init for RWFI
Security policy loaded: Apple Mobile File Integrity (AMFI)
calling smp_policy_init for Sandbox
Security policy loaded: Seatbelt sandbox policy (Sandbox)
calling smp_policy_init for Quarantine
Security policy loaded: Quarantine policy (Quarantine)
calling smp_policy_init for TMSafetyNet
Security policy loaded: Safety net for Time Machine (TMSafetyNet)
Darwin Image Validator Version 2.2.0: Thu Nov 21 20:42:10 PST 2019; root:AppleImage4-61.60.4-474/AppleImage4/RELEASE_ARM64
IDRPIC: Version 0x20 Vectors 64:1111
RCPI Error: [\_SB\_PCI0.RP05.PXSX] Namespace lookup failure, RE_NOT_FOUND (20160930/download2-274)

No Local Variables are initialized for method [PKSK]
No Arguments are initialized for method [PKSK]

RCPI Exception: RE_NOT_FOUND, During name lookup/catalog (20160930/psobject-310)
RCPI Error: Method param/execution failed [\_SB\_PCI0.RP04.PXSX] (Node ffffffffefebdf930), RE_NOT_FOUND (20160930/paparse-632)
RCPI Error: [\_SB\_PCI0.RP05.PXSX] Namespace lookup failure, RE_NOT_FOUND (20160930/download2-274)

No Local Variables are initialized for method [PKSK]
No Arguments are initialized for method [PKSK]

RCPI Exception: RE_NOT_FOUND, During name lookup/catalog (20160930/psobject-310)
RCPI Error: Method param/execution failed [\_SB\_PCI0.RP08.PXSX] (Node ffffffffefebdf70), RE_NOT_FOUND (20160930/paparse-632)
RCPI: Executed 49 blocks of module-level executable ARM code
RCPI: sleep states S3 S4 S5
pci build 04:05:15 Nov 2019, flags 0x20c3000
MID: Legacy shim 2
[ PCI configuration begin ]
console relocated to 0x7f80000000
[ PCI configuration end, bridges 5, devices 12 ]
AppleHWReset failed: { 0 != data } ReleaseIDNode file: /BuildRoot/Library/Caches/com.apple.xbs/Sources/IOHWFamily/IOHWFamily-470.40.4/IOHWController.cpp line: 5416
virtual IOReturn IOHWController::CreateSubmissionQueue(uint16_t, uint8_t):2016:5Q index=0 entrysize=64
virtual IOReturn IOHWController::CreateSubmissionQueue(uint16_t, uint8_t):2016:5Q index=1 entrysize=64
apple_module_start:1669: load: com.apple.filesystems.apfs, v1412.61.1, apfs-1412.61.1, 2019/11/20
SMCSuperIO: sio @ detected device NuVoton NCT6793D
```