

Gigabyte Z390 DESIGNARE: OpenCore-EFI-Ordner und Anleitung

Beitrag von „JimSalabim“ vom 1. April 2020, 13:02

[macdream](#) Siehe auch hier, hab ich gerade gefunden:

<https://github.com/acidanthera.../Manual/FAQ.IntelHD.en.md>

```
Intel UHD Graphics 610-655 (Coffee Lake processors)
Supported since macOS 10.14
CFL framebuffer list:
- 0x3EA50009 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3E920009 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3E980009 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3EA50000 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3E920000 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3E000000 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3E980000 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3EA50004 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3EA50005 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3EA60005 (mobile, 3 connectors, no fbmem, 58 MB)
- 0x3E980006 (mobile, 1 connectors, no fbmem, 39 MB)
- 0x3E980008 (mobile, 1 connectors, no fbmem, 58 MB)
- 0x3E980007 (desktop, 3 connectors, no fbmem, 58 MB)
- 0x3E920003 (desktop, 0 connectors, no fbmem, 1 MB)
- 0x3E910003 (desktop, 0 connectors, no fbmem, 1 MB)
- 0x3E980003 (desktop, 0 connectors, no fbmem, 1 MB)
* Spoiler: CFL connectors
Recommended framebuffers: for desktop - 0x3EA50000 (default), 0x3E9B0007 (recommended); for laptop - 0x3EA50009 (default).
If you are using a 9th generation Coffee Lake Refresh processor, it is necessary to take 'device-id: 923E9888' for iGPU.
Starting with macOS 10.14.4 the fake is not necessary.
```

Es kommt offensichtlich drauf an, ob der Prozessor ein Coffee Lake, Kaby Lake, Skylake oder Broadwell etc. ist.

Du solltest also (da es bei dir um einen **Desktop**-Rechner mit **Coffee-Lake**-Prozessor geht) den empfohlenen Wert 0x3E9B0007 verwenden (also einzutragen als <07009B3E>). Die hab ich auch in meinem "nur-iGPU"-Ordner.

Wie man sieht, kann die device-id auch raus (ab macOS 10.14.4).