

Erledigt

Hackintool Anleitung USB-Patching in Deutsch

Beitrag von „bobpedro“ vom 25. April 2020, 21:34

[iPhoneTruth](#) das Problem beim Befolgen Deiner Anleitung beginnt schon beim Entfernen der SSDT-EC.aml. Ohne die Datei startet mein System leider nicht und bleibt beim "apfs_module_start" hängen:

```
NOPI: sleep status 53 54 55
CPU Sensors: CPU Family 860, model 8c2a, stepping 8c7, cores 4, threads 8, Tjmax 90
CPU Sensors: setting platform keys to 0x42
CPU Sensors: base CPU multiplier is 34
CPU Sensors: started
SMC Sensors: [Error] Unable to validate Dell SMC signature, not loading SMC Sensors
RSC: Only single ROM bank (128 bytes)
pci (build 21:27:24 Jan 9 2020), flags 0x20c1000
SSD: Legacy sata 2
FakeSMC v0.26-757-gc0d829ea.1000 Copyright 2017 rnhias, slice, ian-mas2, kaziak, xmi1, The KING, Babubhai
FakeSMCKeyStore: [Warning] blocked while trying to set protected key "True".
FakeSMC: 10 preconfigured keys added
FakeSMC: 3 keys reported by Clover EFI
SMC: successfully initialized
NOPI Sensors (1200): 1 sensor added (name relocated to 0x00000000)
[ PCI configuration and bridges 9, devices 17 ]
Controller: Intel Cougar Point (vendor ID: 8086, device ID: 1c20)
Controller: HII (unknown) (vendor ID: 1862, device ID: adf0)
error: wrong controller number 0
TIMEST received=1, sent=1, received=0
SuperIODevice: Intel Nuvoton NCT6770Z on port-0x2e address-0x290
TIMEST received=1, sent=1, received=0
error: codec #3 is not responding, probing aborted
ACPI/Sensors: started
RirPort_Brcm3360: Init RirPortFamily_bests-1500.2 "RirPortFamily_bests-1500.2" Jan 9 2020 21:50:12
RirPort: 2.314526: RirPort_Brcm3360 probe: thislib0905d0756ff49d5 score(1110)
FakePCIID: Version 1.3.15 starting an OS X kernel 19.3
apfs_module_start(1683): load: com.apple.filesystems.apfs, +1412.01.1, apfs-1412.01.1, 2020/01/09
```