

# Lenovo Thinkpad T530

Beitrag von „antukst“ vom 28. Oktober 2020, 19:33

```
DK: AppleUserHIDEventDriver-0x10000041d::start(IIONIDInterface-0x100000417) ok
+- AppleHIDDriver::layoutLoadCallback ( <ptr>, 4, 0, <ptr>, 7411 )
HID: Legacy shla 2
DK: AppleUserHIDEventDriver-0x100000422::start(IIONIDInterface-0x10000041b) ok
+- AppleHIDDriver::layoutLoadCallback ( <ptr>, 5, 0, <ptr>, 7411 )
HID: Legacy shla 2
DK: AppleUserHIDEventDriver-0x100000424::start(IIONIDInterface-0x100000421) ok
Wed Oct 28 18:28:27 2020 MacBook-Pro.local com.apple.xpc.launchd[1] (com.apple.xpc.launchd.domain.system) <Notice>; entering bootstrap mode
Wed Oct 28 18:28:27 2020 MacBook-Pro.local com.apple.xpc.launchd[1] (MyListenerSocket) <Error>; No PATH environment variable set. The application firewall will not w
lth this service.
Wed Oct 28 18:28:27 2020 MacBook-Pro.local com.apple.xpc.launchd[1] (MyListenerSocket) <Error>; No PATH environment variable set. The application firewall will not w
lth this service.
Wed Oct 28 18:28:27 2020 MacBook-Pro.local com.apple.xpc.launchd[1] (com.apple.xpc.launchd.domain.system) <Notice>; exiting bootstrap mode
Wed Oct 28 18:28:27 2020 MacBook-Pro.local com.apple.xpc.launchd[1] (com.apple.xpc.launchd.domain.system) <Notice>; entering bootstrap mode
Wed Oct 28 18:28:27 2020 MacBook-Pro.local com.apple.xpc.launchd[1] (com.apple.webcontentfilter.dns) <Notice>; This service is defined to be constantly running and is
arently inefficient.
Wed Oct 28 18:28:27 2020 MacBook-Pro.local com.apple.xpc.launchd[1] (com.apple.xpc.launchd.domain.system) <Notice>; exiting bootstrap mode
ACPI Exception: AE_BAD_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evrgltn-300)
[GBIF] @00015 @0020: SMM
No Local Variables are initialized for method [GBIF]

Initialized Arguments for Method [GBIF]: (0 arguments defined for method invocation)
Arg0: ffffffff3365d6530 <Obj> Integer 0000000000000000
Arg1: ffffffff3365d6f320 <Obj> Package ffffffff33654fb320
Arg2: ffffffff3365d6d30 <Obj> Integer 0000000000000001

ACPI Error: Method parse/execution failed [\_SB_.PCI0.LPC.EC.GBIF] (Node ffffffff33651c630), AE_BAD_PARAMETER (20160930/psparse-632)
ACPI Error: Method parse/execution failed [\_SB_.PCI0.LPC.EC.BAT0._BIF] (Node ffffffff33651c810), AE_BAD_PARAMETER (20160930/psparse-632)
ACPI Exception: AE_BAD_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evrgltn-300)
[GBST] @00050 @0020: SMM

Initialized Local Variables for method [GBST]:
Local0: ffffffff3365d6d30 <Obj> Integer 0000000000000000

Initialized Arguments for Method [GBST]: (0 arguments defined for method invocation)
Arg0: ffffffff3365d6650 <Obj> Integer 0000000000000000
Arg1: ffffffff3365d6f50 <Obj> Integer 0000000000000001
Arg2: ffffffff3365d6f50 <Obj> Integer 0000000000000001
Arg3: ffffffff33654fb2d0 <Obj> Package ffffffff33654fb2d0

ACPI Error: Method parse/execution failed [\_SB_.PCI0.LPC.EC.GBST] (Node ffffffff33651c660), AE_BAD_PARAMETER (20160930/psparse-632)
ACPI Error: Method parse/execution failed [\_SB_.PCI0.LPC.EC.BAT0._BST] (Node ffffffff33651c370), AE_BAD_PARAMETER (20160930/psparse-632)
disk0: I/O error.
lfnst_attach: All kernel threads created for Interface s0 have been scheduled at least once. Proceeding.
IOConsoleUsers: time(0) 0->0, lin 0, lik 1,
IOConsoleUsers: gIOScreenLockState 3, hs 0, ls 0, now 0, sm 0x0
ERROR: FireWire unable to determine security-mode; defaulting to full-secure.
```

Dear [PDM](#)

Rejult show me again