

OpenCore mit Ice Lake

Beitrag von „Peam“ vom 30. Oktober 2020, 20:00

Wie kann ich die denn ändern? Weiß ich ehrlich gesagt gar nicht, sorry 😊 ich dachte das geht nur im Betriebssystem und hat was mit dem WLAN zu tun

Edit: Ohne geänderter MAC Adresse sieht's so aus:

```
AppleCredentialManager: start: started, instance = <ptr>
AppleCredentialManager: start: returning, result = true, instance = <ptr>
AppleKeyStore starting (BUILT: Sep 1 2020 00:56:24)
AppleKeyStore::start: _kernel_relay_enable = 0
AppleKeyStore::start: _sep_enabled = 0
AppleThunderboltGenericHARL::probe
VoodooI2CPCILakeController::pci8086,34e8 Starting I2C controller
AppleThunderboltGenericHARL::start
VoodooI2CPCILakeController::pci8086,34e9 Starting I2C controller
VoodooI2CPCILakeController::pci8086,34e9 Set PCI power state D0
SMCSuperIO      ssio: 0 starting up SuperIO sensors
SMCSuperIO      ssio: 0 failed to detect supported SuperIO chip
VoodooI2CPCILakeController::pci8086,34e9 Current CPU is Comet Lake or Ice Lake, patching...
VoodooI2CPCILakeController::pci8086,34e9 Publishing nub
AppleNVMe Assert failed: ( 0 != data ) VoodooI2CControllerDriver::pci8086,34e9 Probing controller
VoodooI2CControllerDriver::pci8086,34e9 Found valid Synopsys component, continuing with initialisation
VoodooI2CPCILakeController::pci8086,34e8 Set PCI power state D0
VoodooI2CPCILakeController::pci8086,34e8 Current CPU is Comet Lake or Ice Lake, patching...
VoodooI2CControllerNub::pci8086,34e9 SSCN not implemented in ACPI tables
VoodooI2CPCILakeController::pci8086,34e8 Publishing nub
VoodooI2CControllerDriver::pci8086,34e8 Probing controller
VoodooI2CControllerNub::pci8086,34e9 FMCH not implemented in ACPI tables
VoodooI2CControllerDriver::pci8086,34e8 Found valid Synopsys component, continuing with initialisation
VoodooI2CControllerDriver::pci8086,34e9 Warning: Error getting bus config, using defaults where necessary
VoodooI2CControllerNub::pci8086,34e8 SSCN not implemented in ACPI tables
VoodooI2CControllerNub::pci8086,34e8 FMCH not implemented in ACPI tables
ReleaseIDNode VoodooI2CControllerDriver::pci8086,34e8 Warning: Error getting bus config, using defaults where necessary
file: /AppleInternal/BuildRoot/Library/Caches/com.apple.xbs/Sources/IONVMeFamily/IONVMeFamily-479.100.17/IONVMeController.cpp: VoodooI2CController
line: 5478
VoodooI2CControllerDriver::pci8086,34e9 Publishing device nubs
Thunderbolt runtime power conservation disabled.
virtual IOReturn IONVMeController::CreateSubmissionQueue(uint16_t, uint8_t)::2861:SQ index=0 entriSize=64
virtual IOReturn IONVMeController::CreateSubmissionQueue(uint16_t, uint8_t)::2861:SQ index=1 entriSize=64
apfs_module_start:1689: load: com.apple.filesystems.apfs, v1412.141.1, apfs-1412.141.1, 2020/08/31
```