


```
initwithController: Setting fWlanRanging80MHzBootArg to 0
I080211Controller::start_controller is 0x5fab1125833da95b, provider is 0x5fab11258357a35b
ARPT: 3.355002: srom rev:11
ARPT: 3.365714: ChangeVCO => vco:960, xtalF:40, frac: 90, ndivMode: 3, ndivint: 24
ARPT: 3.377642: Data written into the PLL_CNTRL_ADDR2: 00000c31
ARPT: 3.389180: Data written into the PLL_CNTRL_ADDR3 (Fractional): 0000100e
Init: error getting PHY_MODE; using MODE_UNKNOWN
ARPT: 3.425016: BCM tunables:
ARPT: 3.435499: pullmode[1] txringsize[ 256] txsendqsize[0] reapmin[ 32] reapcount[ 120]
ARPT: 3.448911: wl0: Broadcom BCM43a0, vendorID[0x14e4] BAR0[0xb1200004]
7.77.111 (T08) (r852736)
ARPT: 3.470907: Set packet allocation type to 1
apfs_module_start:2436: load: com.apple.filesystems.apfs, v1677.01.1, apfs-1677.01.1, 2021/01/24
cryptoAlloc:674: Using 64 buffers with size 16384, 512 buffers size 65536
swcrypto_threadpool_init:1542: Starting ThreadPool
swcrypto_threadpool_init:1564: 4 threads would be used for the ThreadPool
swcrypto_threadpool_worker_thread:1488: ThreadPool worker thread started
swcrypto_threadpool_worker_thread:1488: ThreadPool worker thread started
swcrypto_threadpool_worker_thread:1488: ThreadPool worker thread started
swcrypto_threadpool_worker_thread:1488: ThreadPool worker thread started
dev_init:297: disk0s2 device accelerated crypto: 0 (compiled @ Jan 24 2021 20:57:23)
dev_init:300: disk0s2 device handle block size 4096 block count 86889754 features 0 Internal
fletcher64_init:106: Selecting AVX2 implementation of fletcher64
```