UEFI SECURE BOOT - WINDOWS 11 UND MONTEREY (DUALBOOT MIT OPENCORE) TEIL 2

Beitrag von „talkinghead“ vom 26. Oktober 2021, 09:01

Hmm...

bricht es bei ./configure ab?

configure versucht über pkg-config die benötigen Header/Libs zu finden.

Gibt das mal ein... und prüfe den Output.

Code

1. sbsigntools-macOS % pkg-config --cflags libcrypto
2. -I/opt/local/libexec/openssl11/include
3.
4. sbsigntools-macOS % pkg-config --libs libcrypto
5. -L/opt/local/libexec/openssl11/lib -lcrypto

Falls du openssl-dev installiert hast, könntest du versuchen in src/Makefile.am -I/pfad_zu_openssl_Header rein bauen

In Zeile 10

```
1
2  bin_PROGRAMS = sbsign sbverify sbattach sbvarsign sbsiglist
3
4  coff_headers = coff/external.h coff/pe.h
5  AM_CFLAGS = -Wall -Wextra --std=gnu99  -Wno-gnu-variable-sized-type-not-at-end
6
7  common_SOURCES = idc.c idc.h image.c image.h fileio.c fileio.h \
8      efivars.h $(coff_headers)
9  common_LDADD = ../lib/ccan/libccan.a $(libcrypto_LIBS)
10 common_CFLAGS = -I$(top_srcdir)/lib/ccan/ -I/opt/local/include -I$(top_srcdir)/ext/ -Werror
11
12 sbsign_SOURCES = sbsign.c $(common_SOURCES)
13 sbsign_LDADD = $(common_LDADD)
14 sbsign_CFLAGS = $(AM_CFLAGS) $(common_CFLAGS)
```