

Erledigt

Clover Yosemite dsmos arrived reboot

Beitrag von „montymotz“ vom 20. Oktober 2014, 00:31

Hallo vielleicht kann ja jemand helfen habe einen Clover USB stick erstellt und dieser funktioniert soweit das ich Booten kann.

Leider startet er sich immer wieder bei dsmos arrived neu (siehe screen)

```
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.speech.synthesis) <Notice>: This key does
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.speech.synthesis) <Error>: The JetsamProperties key is no
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.syslogd) <Error>: The HopefullyExitsLast key is
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.syslogd) <Notice>: Please switch away from OnDem
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.storage.kit) <Notice>: This key does not do anyth
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.TrustEvaluationAgent.system) <Notice>: This key d
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] <Error>: assertion failed: 14A389: launchd + 184274 [5589FF2
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.VoiceOver.running) <Warning>: The HideUntilCheck
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.windowserver.active) <Warning>: The HideUntilCheck
USBF: 8.518 The IOUSBFamily is having trouble enumerating a USB device that has been plugged in. It will keep ret
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.windowserver.active) <Warning>: The HideUntilCheck
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] (com.apple.CoreRAID.111) <Warning>: Endpoint has been activat
Sun Oct 19 18:32:19 2014 localhost com.apple.xpc.launchd[1] <Error>: assertion failed: 14A389: launchd + 181539 [5589FF2
Sun Oct 19 18:32:20 2014 localhost com.apple.xpc.launchd[1] (com.apple.bsd.dirhelper.131) <Warning>: Endpoint has been a
Sun Oct 19 18:32:20 2014 localhost com.apple.xpc.launchd[1] (com.apple.bsd.dirhelper.131) <Warning>: Endpoint has been a
USBF: 9.443 The IOUSBFamily was not able to enumerate a device.
Sun Oct 19 18:32:20 2014 localhost com.apple.xpc.launchd[1] (com.apple.notification) <Warning>: Endpoint has been activat
Sun Oct 19 18:32:20 2014 localhost com.apple.xpc.launchd[1] (com.apple.CoreRAID.111) <Warning>: Endpoint has been activat
Sun Oct 19 18:32:21 2014 localhost com.apple.xpc.launchd[1] (com.apple.xpc.launchd.domain.user.8) <Error>: Could not rea
Sun Oct 19 18:32:21 2014 localhost com.apple.xpc.launchd[1] (com.apple.xpc.launchd.domain.user.8) <Error>: Could not rea
USBF: 10.308 The IOUSBFamily is having trouble enumerating a USB device that has been plugged in. It will keep ret
USBF: 10.621 The IOUSBFamily was not able to enumerate a device.
Sun Oct 19 18:32:21 2014 localhost com.apple.xpc.launchd[1] <Error>: assertion failed: 14A389: launchd + 23644 [5589FF23-
Sun Oct 19 18:32:21 2014 localhost com.apple.xpc.launchd[1] (com.apple.syslogd.121) <Warning>: Endpoint has been activat
Sun Oct 19 18:32:21 2014 localhost com.apple.xpc.launchd[1] (com.apple.syslogd.121) <Warning>: Endpoint has been activat
USBF: 11.105 The IOUSBFamily is having trouble enumerating a USB device after 10 retries. (Port 5 of Hub at 0x14000000)
USBF: 11.198 The IOUSBFamily gave up enumerating a USB device after 10 retries. (Port 5 of Hub at 0x14000000)
SUSBF: 11.218 The IOUSBFamily was not able to enumerate a device.
Sun Oct 19 18:32:22 2014 localhost com.apple.xpc.launchd[1] (com.apple.secd) <Notice>: This key does not do anything: OnDe
Sun Oct 19 18:32:22 2014 localhost com.apple.xpc.launchd[1] (com.apple.secd) <Error>: The ServiceIPC key is no longer res
Sun Oct 19 18:32:22 2014 localhost com.apple.xpc.launchd[1] (com.apple.TrustEvaluationAgent) <Notice>: This key does not
Sun Oct 19 18:32:22 2014 localhost com.apple.xpc.launchd[1] (com.apple.xpc.launchd.domain.user.8) <Error>: Failed to boot
Sun Oct 19 18:32:22 2014 localhost com.apple.xpc.launchd[1] (com.apple.xpc.launchd.domain.user.8) <Error>: Failed to boot
Sun Oct 19 18:32:22 2014 localhost com.apple.xpc.launchd[1] (com.apple.DataDetectors.DynamicData) <Warning>: The JoinExist
hfs: mounted Install OS X Yosemite on device disk15s2
jnl: disk0s2: replay_journal: from: 16523776 to: 16630784 (joffset 0x3ba000)
jnl: disk0s2: journal replay done.
hfs: mounted MacintoshHD on device disk0s2
Sun Oct 19 18:32:29 2014 localhost com.apple.xpc.launchd[1] (MyListenerSocket) <Error>: No PATH environment variable set.
Sun Oct 19 18:32:29 2014 localhost com.apple.xpc.launchd[1] (MyListenerSocket) <Error>: No PATH environment variable set.
Sun Oct 19 18:32:29 2014 localhost com.apple.xpc.launchd[1] (com.apple.webcontentfilter.dns) <Notice>: This service is def
Apple16X58ACPI: Identified Serial Port on ACPI Device=UARR1
Apple16X58UARTSync1: Detected 16558AF/C/CF FIFO=16 MaxBaud=115200
IOGraphics flags 0x43
Previous shutdown cause: 3
IOPPF: XCPM mode
XBGPPlatformShim::sendPStates - Success!
XBGPPlatformShim::sendPStates - Success!
XBGPPlatformShim::sendPStates - Success!
XBGPPlatformShim::sendPStates - Success!
[AGPM Controller] unknownPlatform
Sound assertion in AppleHDADriver at line 1587
Sound assertion in AppleHDADriver at line 2153
Sound assertion in AppleHDADriver at line 194
Sound assertion in AppleHDADriver at line 1851
DSMOS has arrived
```

Wenn ich das hier eingibe KEINE FREMDSPRCHIGEN LINKS LESE DIR REGELN (EDIT Stein)

Code

1. fsck -fy
2. mount -uw /
- 3.
- 4.
5. mkdir /Backup
6. cd /System/Library/Extensions
7. mv -Rf NVD*.kext /Backup
8. mv -Rf ATI*.kext /Backup
9. mv -Rf AppleIntelGMA* AppleIntelHD* AppleIntelSNB* AppleIntelIntegratedFramebuffer* /Backup
10. reboot

kommt

Code

1. diskX : device is write locked

Jemand eine Idee?

Beitrag von „jürgenX“ vom 20. Oktober 2014, 01:17

Ich hatte das gleiche Problem wie du. Ich habe eine Nvidia GTX 590 in meinem Rechner verbaut und folgendes hat geholfen:

Auf der EFI Partition die /CLOVER/config.plist folgendermaßen abändern:

Zitat

```
<key>Graphics</key>  
<dict>  
<key>Inject</key>
```

```
<dict>
<key>ATI</key>
<false/>
<key>Intel</key>
<true/>
<key>NVidia</key>
<true/>
```

Alles anzeigen

Beitrag von „montymotz“ vom 20. Oktober 2014, 08:57

Das führt leider auch zu keiner Lösung 😞

Also in meinem fall halt:

Code

1. <key>Graphics</key>
2. <dict>
3. <key>Inject</key>
4. <dict>
5. <key>ATI</key>
6. <true/>
7. <key>Intel</key>
8. <true/>
9. <key>NVidia</key>
10. <false/>