

Erledigt

AMD mac OS 10.11.4 sound card (with the VoodooHDA) help

Beitrag von „a250995788“ vom 14. Dezember 2016, 15:18

Chameleon (Version: 2389) The boot install partition is in MBR format

Computer Configuration:

Motherboard: Gigabyte GA-A55-S3P

CPU: AMD Athlon II X4 641 Quad-Core Processor

Memory: Kingston DDR3 8GB

Soundcards: Realtek ALC 887 (ID: 10EC0887)

NIC: Realtek 8168

Graphics card: Nvidia GT520 512M

NIC, graphics card has been driven

Sound card with universal boot burst sound, Zizi sound also

Beitrag von „derHackfan“ vom 14. Dezember 2016, 19:38



Herzlich Willkommen im Forum.

Beitrag von „a250995788“ vom 15. Dezember 2016, 00:07

My sound card can use AppleHDA counterfeit with what universal settings to modify

Beitrag von „griven“ vom 15. Dezember 2016, 23:45

Should work with AppleALC.kext and vanilla AppleHDA in /S/L/E.

For ALC887 CodecID 5 should be set in order to make it work. You´ll need to patch your DSDT in order to make it work. If you´re not sure how it has to be done download and install [MacIASL](#) and open it up. It should open up with your current DSDT loaded (if not head over to head over to Files in the top Menu Bar and select new from ACPI and in the upcoming Menu choose dsdt). Once opened again head over to Files and select Save as und save your DSDT als decompiled ASL File and upload it here so we can take care of it 😊

Beitrag von „a250995788“ vom 16. Dezember 2016, 12:44

In the Windows extract dsdt do not compile directly to me to modify the next [acpi_dsdt.dsl](#) In front of this is my upload attachments

Beitrag von „griven“ vom 16. Dezember 2016, 23:18

Sorry dude but this file is not usable/no valid dsl code...

Please extract the DSDT in OS-X as described above otherwise you´ll not be able to edit/patch it...

Beitrag von „a250995788“ vom 17. Dezember 2016, 01:11

Ok! MacOS what software to extract

Beitrag von „a250995788“ vom 17. Dezember 2016, 08:59

Computer Configuration:

Gigabyte A55S3P

CPU x4 641

Sound:Realtek ALC887

LAN:Realtek 8168

Graphics:GT520 512M

Bootloader:Chamelon 2389

install El Capion10.11.4

Configuration as above, video card drive-free network card drive system comes with, VoodooHDA (version: 2.8.8, 2.8.9) can not drive the sound card

Beitrag von „Thogg Niatiz“ vom 17. Dezember 2016, 09:05

Is there a reason why you started a new thread about the same topic? Merged.

Use MaciASL, as griven wrote in his post [AMD mac OS 10.11.4 sound card \(with the VoodooHDA\) help](#)

Beitrag von „a250995788“ vom 17. Dezember 2016, 09:17

Now only windows system can also make it

Beitrag von „Thogg Niatiz“ vom 17. Dezember 2016, 09:25

I'm not sure if i understand what you mean... boot Clover Bootloader, press F4 in Bootscreen to

extract ACPI Files to EFI/Clover/ACPI/origin on your Clover Drive and upload DSDT.aml from there here

Beitrag von „a250995788“ vom 17. Dezember 2016, 23:39

Chameleon installation system with clover extraction feasible?

Beitrag von „al6042“ vom 17. Dezember 2016, 23:41

Chameleon and Clover are two different Bootloaders for Hackintosh...
What do you mean with "Chameleon installation system with clover extraction feasible?"

Beitrag von „a250995788“ vom 18. Dezember 2016, 12:34

<p>AMD chameleon boot installation system can dsdt driver sound card</p>

Beitrag von „al6042“ vom 18. Dezember 2016, 12:56

I still cannot not understand what you are trying to tell or ask us...
If english is not you native language, please ask your questions at the international section from insanelyMac:

<http://www.insanelymac.com/forum/forum/214-international/>

Beitrag von „a250995788“ vom 24. Dezember 2016, 23:37

AppleHDA.kext with the original version of AppleHDA Patcher to drag and drop files generated after how to modify the node

Beitrag von „al6042“ vom 24. Dezember 2016, 23:45

Should this be a question or just some information?

Beitrag von „a250995788“ vom 26. Dezember 2016, 11:31

<p>this is a questions</p>

Beitrag von „al6042“ vom 26. Dezember 2016, 11:51

In that case, we have still the same issue as a couple of days before:

Zitat

I still cannot not understand what you are trying to tell or ask us....

If english is not you native language, please ask your questions at the international section from insanelyMac:

[insanelymac.com/forum/forum/214-international/](https://www.insanelymac.com/forum/forum/214-international/)

Beitrag von „derHackfan“ vom 26. Dezember 2016, 12:30

[@a250995788](#) Please add your profile (Mainboard, CPU, Graphic Card, etc.) and tell us your problem. 🤔

Beitrag von „a250995788“ vom 26. Dezember 2016, 15:10

OK Setup is complete

Beitrag von „derHackfan“ vom 26. Dezember 2016, 17:35

Benutze bitte den Google Übersetzer ... 👍

Du hast ein Gigabyte FM1 Sockel inklusive Realtek ALC887 Chip, entweder läuft der Sound mit dem AppleALC.kext oder nicht, kommt immer auf einen Versuch an.

Mit Clover musst du in der config.plist einen Haken unter ACPI bei FixHDA setzen, möglich Layout ID's wären 1, 2, 3, 5, 7, 11, 13, 17, 18, 33 und 99, jene müssen unter Devices und da unter Audio eingetragen werden.

Siehe Bild ...

