

ASUS Sabertooth X99

Beitrag von „SI6sh“ vom 13. Juli 2021, 22:25



- Audio: Realtek ALC1150 (AppleALC.kext, layout-id=99)
- 1Gbit Ethernet (Intel I218V, Realtek 8111GR)
- **Inkompatibilitäten:** kein SideCar
- **macOS und SMBios:** ab macOS Catalina 10.15.7 und Big Sur 11.4 iMacPro1,1
- **EFI Ordner:** siehe Anhang
- **BIOS Settings:**

- **AI Tweaker:**

- ASUS Multicore Enhancement -- Disabled

- Internal PPL Overvoltage -- Disabled

- AI Overclock Tuner: XMP

- CPU Core Ratio: Sync All Cores

- Core Ratio: 42

- Manual Voltage: 1.35v

- Advanced**

- Intel (VMX) Virtualization Technology: Enabled

- CPU Configuration > Power Management Configuration

- Enhanced Intel SpeedStep Technology -- Disabled

- Turbo mode: Enabled

- CPU C-State: Enabled

- USB Configuration

- Intel xHCI Mode: Enabled

EHCI Legacy Support: Enabled
xHCI Hand-off: Enabled
EHCI Hand-off -- Enabled

Onboard Devices Configuration:
SPDIF Out Type: HDMI

Boot

Fast Boot: Disabled
Boot Logo Display: Full Screen
NumLock State: Disabled
Above 4G Decoding: Enabled
Setup Mode: Advanced

CSM (Compatibility Support Module)

Launch CSM: Disabled

Secure Boot

OS Type: Other OS