

ASUS Sabertooth X99

Beitrag von „SI6sh“ vom 13. Juli 2021, 22:25



- Audio: Realtek ALC1150 (AppleALC.kext, layout-id=99)
- 1Gbit Ethernet (Intel I218V, Realtek 8111GR)
- **Inkompatibilitäten:** kein SideCar
- **macOS und SMBios:** ab macOS Catalina 10.15.7 und Big Sur 11.4 iMacPro1,1
- **EFI Ordner:** siehe Anhang
- **BIOS Settings:**

- **AI Tweaker:**

ASUS Multicore Enhancement -- Disabled

Internal PPL Overvoltage -- Disabled

AI Overclock Tuner: XMP

CPU Core Ratio: Sync All Cores

Core Ratio: 42

Manual Voltage: 1.35v

Advanced

Intel (VMX) Virtualization Technology: Enabled

CPU Configuration > Power Management Configuration

Enhanced Intel SpeedStep Technology -- Disabled

Turbo mode: Enabled

CPU C-State: Enabled

USB Configuration

Intel xHCI Mode: Enabled

EHCI Legacy Support: Enabled
xHCI Hand-off: Enabled
EHCI Hand-off -- Enabled

Onboard Devices Configuration:
SPDIF Out Type: HDMI

Boot

Fast Boot: Disabled
Boot Logo Display: Full Screen
NumLock State: Disabled
Above 4G Decoding: Enabled
Setup Mode: Advanced

CSM (Compatibility Support Module)

Launch CSM: Disabled

Secure Boot

OS Type: Other OS